



SPECIFICATIONS

MBA Grande Rigid Core 6mm with Acoustic Pad

Overall Thickness	6MM (4.5MM RIGID CORE WITH 1.5MM IXPE PAD)
Plank Size	9"X60"X6MM
Wear Layer	.3MM (12MIL) WITH CERAMIC FINISH
Printed Design	WOOD VISUAL EMBOSSING
Surface Finish	UV CURED COATING WITH 7% GLOSS
Edge Profile	12 COLORS; 4 SIDED MICRO BEVEL
Installation	VALINGE 2G ANGLE-ANGLE SYSTEM FLOATING
Impact Isolation class	IIC 73
Sound Transmission Class	STC 71
Phthalate Free	E1
Slip Resistance	DS
Fire Behavior	B FL S1
Indoor Air Quality	FLOOR SCORE
Recyclable	100%
Dimensional Stability	ASTM F2199-09(2014)PASS
Resistance to Chemicals	ASTM F925-13 PASS
Abrasion Resistance	ASTM D4060-14 SCRATCH RESISTANCE
In floor heating	IN SLAB, RADIANT HEAT ONLY MAX (28 DEGREE CELSIUS)
Limited warranty	LIFETIME RESIDENTIAL AND 10 YEAR LIMITED COMMERCIAL
Packaging: Plank/box	6
Coverage: Sq.Ft/Box	22.11 or 22.43
Weight	45 LBS
ALL Mouldings-94"	EXACT MATCH, FLUSH NOSING, REDUCER, T-MOULDING



Installation type:
Floating



CERTIFIED BY
SCS Global Services

