



AEDELED30/CW/PIR



Features

Compact and economic aluminium LED floodlight

Only suitable for semi commercial applications

30W comparable light output of 35W HQI

Bracket design allows installation without removing mounting bracket

PIR versions complete with manual override facility

Pre-wired with 1 metre of rubber insulated cable for ease of installation

Cool white and warm white options available

LED lifespan L90 36,000 hours

Non-dimmable

General Information

| | |
|--------------------------------|-------------------|
| Lamp Type | LED |
| Colour / Finish | Black |
| IP Rating | IP44 |
| IK Rating | IK06 |
| Class Protection | 1 |
| Internal / External | Internal/External |
| Surface / Recessed / Suspended | Surface |
| Warranty (Years) | 2 |
| CE Mark | Yes |
| Length (mm) | 193 |
| Width (mm) | 167 |
| Depth (mm) | 57 |

Technical Information

| | |
|------------------|-----------|
| Wattage | 30W |
| Lumens Delivered | 2762lm |
| Lm/W | 92lm |
| CRI | Ra 80 |
| CCT | 4000K |
| Input | 220-240V |
| Hertz | 50/60hz |
| Operating Temp | -20 to 40 |

Datasheet generated from <https://onetimepim.com> last updated Friday, March 26, 2021 11:29:19 AM

