



ANZOLED/CCT



Features

Ultra-slim adjustable LED performance downlight

Only suitable for semi commercial applications

Integral switches for multiple wattages and selectable CCT

Innovative bracket / spring design for variable cutouts from 65-205mm

Pre-wired with 300mm cable

LED lifespan L70 54,000 hours

Non-dimmable

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface / Recessed
Warranty (Years)	3
CE Mark	Yes
Diameter (mm)	235
Height (mm)	16

Technical Information

Wattage	10W/13W/16W
Lumens Delivered	1027lm/1309lm/1492lm (3000K, 10W/13W/16W), 1077lm/1409lm/1636lm (4000K, 10W/13W/16W), 1045lm/1351lm/1555lm (6000K, 10W/13W/16W)
Lm/W	103lm/101lm/93lm (3000K, 10W/13W/16W), 108lm/108lm/102lm (4000K, 10W/13W/16W), 105lm/104lm/97lm (6000K, 10W/13W/16W)
CRI	Ra 80
CCT	3000K/4000K/6000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 45°C

Datasheet generated from <https://onetimepim.com> last updated Tuesday, March 30, 2021 8:29:49 AM

