



APACLED1/60/CW



Features

High performance maintenance free LED panel

Suitable for installation in offices, educational buildings, retail and healthcare premises

Slimline design allows for installation into shallow ceiling voids

TPa as standard

UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort

Cool white, warm white and daylight options

Self-Test Panel Pod and Sensor Pod compatible

Powered by Philips

LED lifespan L80 B10 54,000 hours

Dimmable and OCTO options available

General Information

Lamp Type	LED
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface/Recessed/Suspended
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Height (mm)	36
Accessories	AIRMLLED/POD/3NM/ST, AIRMLLED/POD/MWS, APACLED/SK, AERMLED/60/SMF

Technical Information

Wattage	28W
Lumens Delivered	3300lm
Lm/W	118lm
CRI	Ra 80
CCT	4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-10°C to 45°C

Datasheet generated from <https://onetimepim.com> last updated Tuesday, April 6, 2021 10:49:55 AM

