



LL-D4-BK

ASSEMBLY INSTRUCTIONS

ASSEMBLY STEPS:

1. REMOVE MOUNTING BRACKET FROM FIXTURE. INSTALL THE BRACKET TO THE JUNCTION BOX. ENSURE THAT THE TWO SCREW THREADS ARE POINTING AWAY FROM THE WALL AND ARE IN THE HORIZONTAL POSITION.
2. CONNECT THE WHITE WIRE FROM THE FIXTURE WITH THE WHITE SUPPLY WIRE FROM THE WALL USING THE WIRE CONNECTOR. CONNECT THE BLACK WIRE FROM THE FIXTURE TO THE BLACK (OR RED) SUPPLY WIRE FROM THE WALL. CONNECT THE GROUND WIRE TO THE COPPER WIRE USING THE WIRE CONNECTOR.
3. PUSH THE WIRES INTO THE JUNCTION BOX. MOUNT THE FIXTURE ONTO THE MOUNTING BRACKET AND SECURE WITH THE FIXATION SCREWS.
4. INSTALL THE LIGHT BULBS, AND PUSH BOTH END CAPS INTO POSITION. MAXIMUM 100 WATTS.
5. APPLY SEALANT TO SEAL THE SIDES AND TOP OF THE FIXTURE TO THE WALL. DO NOT SEAL BOTTOM SIDE OF THE BACKPLATE TO ALLOW MOISTURE TO DRAIN.

CAUTION: PULL ANY EXCESS WIRE THROUGH BOTTOM OF THE LAMP. PLEASE USE TYPE A BULB. DO NOT USE LIGHT BULB RATED GREATER THAN 100 WATTS OR THE LAMP MAY BURN AND CAUSE A FIRE! TO CLEAN, USE A SOFT CLOTH ONLY.

NOTE: TURN THE POWER OFF (UNPLUG FROM THE WALL OUTLET) BEFORE REPLACING THE BULB. MAKE SURE THE BULB HAS SUFFICIENT TIME TO COOL DOWN. DO NOT SUBJECT THE LAMP TO ANY SHOCK WHILE LIT AS SHATTERING OF LAMP MAY RESULT.

