

LINEA DI LIARA

LL-P415-CB/LL-P415-SS/LL-P415-LP

ASSEMBLY INSTRUCTIONS

ASSEMBLY STEPS:

1. SCREWS SOCKET [A] AND THE CENTER RODS [B] TO CANOPY [C].
2. FIX THE MOUNTING BAR [F] ONTO THE JUNCTION BOX AND TIGHTEN BY SCREWS [G].
3. CONNECT THE BLACK WIRE OF LAMP WITH THE BLACK WIRE ON CEILING BRACKET BY CONNECTOR [I]; CONNECT WHITE WIRE OF LAMP WITH WHITE WIRE ON CEILING BRACKET BY CONNECTOR [I]. CONNECT THE GROUND WIRE WITH THE GROUND WIRE ON CEILING BRACKET BY CONNECTOR [H].
4. SECURE THE CANOPY [C] ONTO THE MOUNTING BAR [F] THEN TIGHTEN WITH THE SCREWS [J].
5. POSITION THE GLASS [D] ONTO LAMP AND SECURE WITH SCREWS [E].
6. SCREW THE BULB ONTO SOCKET (BULB NOT INCLUDE).

CAUTION: PULL ANY EXCESS WIRE THROUGH BOTTOM OF THE LAMP. PLEASE USE TYPE A BULB. DO NOT USE LIGHT BULB RATED GREATER THAN 100 WATTS OR THE LAMP MAY BURN AND CAUSE A FIRE! TO CLEAN, USE A SOFT CLOTH ONLY.

NOTE: TURN THE POWER OFF (UNPLUG FROM THE WALL OUTLET) BEFORE REPLACING THE BULB. MAKE SURE THE BULB HAS SUFFICIENT TIME TO COOL DOWN. DO NOT SUBJECT THE LAMP TO ANY SHOCK WHILE LIT AS SHATTERING OF LAMP MAY RESULT.

