

LINEADILIARA

LL-P719

ASSEMBLY INSTRUCTIONS

ASSEMBLY STEPS:

1. FIX THE MOUNTING BAR [B] ONTO THE JUNCTION BOX AND TIGHTEN BY SCREWS [C].
2. LOOSEN THE SCREW BY SCREWDRIVER FOR ADJUSTING THE LENGTH OF FLEXIBLE CORD. RE-TIGHTEN THE SCREW AFTER ADJUSTING.
3. CONNECT THE BLACK WIRE (LIVE WIRE) OF LAMP WITH THE BLACK WIRE (LIVE WIRE) ON CEILING BRACKET BY CONNECTOR [E]; CONNECT WHITE WIRE (NULL WIRE) OF LAMP WITH WHITE WIRE (NULL WIRE) ON CEILING BRACKET BY CONNECTOR [F]. CONNECT THE GROUND WIRE WITH THE GROUND WIRE ON CEILING BRACKET BY CONNECTOR [D].
4. PLACE THE LIGHTING FIXTURE [A] ONTO THE MOUNTING BAR [C], AND ATTACH BY SCREWING NUTS [F].
5. SCREW THE BULB ONTO SOCKET (BULB NOT INCLUDE).

CAUTION: PULL ANY EXCESS WIRE THROUGH BOTTOM OF THE LAMP. PLEASE USE TYPE A BULB. DO NOT USE LIGHT BULB RATED GREATER THAN 100 WATTS OR THE LAMP MAY BURN AND CAUSE A FIRE! TO CLEAN, USE A SOFT CLOTH ONLY.

NOTE: TURN THE POWER OFF (UNPLUG FROM THE WALL OUTLET) BEFORE REPLACING THE BULB. MAKE SURE THE BULB HAS SUFFICIENT TIME TO COOL DOWN. DO NOT SUBJECT THE LAMP TO ANY SHOCK WHILE LIT AS SHATTERING OF LAMP MAY RESULT.

