



STX-SC5

ASSEMBLY INSTRUCTION

ASSEMBLY STEPS:

1. REMOVE WALL BRACKET FROM THE LAMP FIXTURE, AND ATTACH THE MOUNTING CROSS BAR [A] ONTO THE WALL BRACKET ON THE WALL AND FASTENING WITH THE MOUNTING SCREWS [B].
2. CONNECT THE BLACK CORD OF LAMP WITH THE ANODE WIRE ON WALL BRACKET BY CONNECTOR [I], CONNECT WHITE CORD OF LAMP WITH CATHODE WIRE ON WALL BRACKET BY CONNECTOR [I]. CONNECT THE GROUND WIRE TO WALL BRACKET BY CONNECTOR [J].
3. PLACE THE BACKPLATE [K] ON THE MOUNTING CROSS BAR [A] AND TIGHTEN BY SCREWING [L].
4. SLIP THE GLASS SHADE [C] ONTO [E].
5. PUT THE TWO END PARTS [G] ON TWO ENDS OF GLASS SHADE [C] AND TIGHTEN BY NUT [F].
6. LOCK THE GLASS SHADE [C] BUY SCREW NUT [H] TIGHTENLY.

CAUTION:PULL ANY EXCESS WIRE THROUGH BOTTOM OFTHE LAMP, .PLEASE USE TYPE A BULB.DO NOT USE LIGHT BULB RATED GREATER THAN 40 WATTS OR THE LAMP MAY BURN AND CAUSE A FIRE! TO CLEAN,USE A SOFT CLOTH ONLY.

NOTE 1:TURN THE POWER OFF(UNPLUG FROM THE WALL OUTLET) BEFORE REPLACING THE BULB .MAKING SURE THE BULB HAD SUFFICIENT TIME TO COOL DOWN. DO NOT SUBJECT TO THE LAMP TO ANY SHOCK WHITE LIT AS SHATTERING OF LAMP MAY RESULT.

NOTE 2:CLEAN THE LIGHTING FIXTURE GENTLY WITH A DRY, SOFT CLOTH.

