

LINEA DILIARA

LL-WL688

ASSEMBLY INSTRUCTION

ASSEMBLY STEPS:

1. REMOVE WALL BRACKET FROM THE LAMP FIXTURE, AND ATTACH THE MOUNTING BAR [A] ONTO THE WALL AND FASTEN WITH THE MOUNTING SCREWS [D].
2. CONNECT THE BLACK WIRE OF LAMP WITH THE BLACK WIRE ON WALL BRACKET BY CONNECTOR [B], CONNECT WHITE WIRE OF LAMP WITH WHITE WIRE ON WALL BRACKET BY CONNECTOR [C]. CONNECT THE GROUND WIRE TO WALL BRACKET BY CONNECTOR [B].
3. PLACE THE LAMP FIXTURE [E] ON THE MOUNTING BAR [A] AND TIGHTEN BY NUT [F].
4. INSTALL THE BULBS (BULB NOT INCLUDED).
5. SLIP THE GLASS SHADE [H] BETWEEN CIRCLE PART [G] AND METAL PART [K].
6. LOCK THE GLASS SHADE [H] BY SCREW NUT [J]. MAKE SURE THE GLASS SHADE IS SECURED BY SCREW NUT [J].

CAUTION: PULL ANY EXCESS WIRE THROUGH BOTTOM OF THE LAMP, PLEASE USE TYPE B BULB. DO NOT USE LIGHT BULB RATED GREATER THAN 40 WATTS OR THE LAMP MAY BURN AND CAUSE A FIRE!

NOTE 1: TURN THE POWER OFF (UNPLUG FROM THE WALL OUTLET) BEFORE REPLACING THE BULB. MAKING SURE THE BULB HAD SUFFICIENT TIME TO COOL DOWN. DO NOT SUBJECT TO THE LAMP TO ANY SHOCK WHILE LIT AS SHATTERING OF LAMP MAY RESULT.

NOTE 2: CLEAN THE LIGHTING FIXTURE GENTLY WITH A DRY, SOFT CLOTH.

