

CC6571D LIQUID COOLED SAW

Cool Running, Fuel Efficient and Reliable 71 HP Kubota® Diesel



Blade not included



Tier 4 Final

Powered By:



CC6571D Saw

14"-42" Blade Capacity

Diesel

Features & Benefits:

- Tier 4 Final liquid-cooled engine allows for a smoother running, longer lasting saw with higher productivity
- Easy to maneuver self propelled drive
- Strongest frame on the market
- Less rear weight for easy maneuvering and reduced operator fatigue
- Oil bath blade shaft comes standard
- One-hand sawing control and parking brake
- Fits through a 36" wide door frame (when guard is removed)
- Quick release blade flange
- Blade shaft tachometer-where it's needed-not at the engine, gives true blade speed

CC6571D SPECIFICATIONS

Max. Depth of Cut with 14" Blade	4-1/2" (3-3/4" 3-speed)
Max. Depth of Cut with 20" Blade	7-1/2" (6-3/4" 3-speed)
Max. Depth of Cut with 26" Blade	10-1/2" (9-3/4" 3-speed)
Max. Depth of Cut with 30" Blade	11-3/4" (11-3/4" 3-speed)
Max. Depth of Cut with 36" Blade	14-3/4" (14-3/4" 3-speed)
Max. Depth of Cut with 42" Blade	17-3/4" (17-3/4" 3-speed)
Blade Shaft Diameter	2"
Arbor Size	1" with single drive pin
Blade Shaft Drive	10 belts
Blade Mounting	Right or Left
Blade Raise/Lower	Electro-hydraulic pump
Transmission	Eaton Model 10
Drive Speed	0-200 feet per minute
Air Filter	4-stage
Fuel Capacity	9 gallons

Includes

Blade shaft tachometer, Hour meter, Frame lift, Telescoping front pointer, Parking brake, Cutting depth indicator, Quick disconnect blade flanges, Oil bath blade shaft

CC6571D DIESEL LIQUID COOLED WALK BEHIND SAW

Saw Model #	Engine/Motor Make	Speeds	Engine/Motor Power	Power Source	Blade Capacity	Part #	Cat #	Product Weight (lbs.)	List Price
CC6571D-14	Kubota®	Single	71 HP	Diesel	14"	5801160	55603	1,825	\$39,496
CC6571D-20	Kubota®	Single	71 HP	Diesel	20"	5801161	55625	1,835	39,605
CC6571D-26	Kubota®	Single	71 HP	Diesel	26"	5801162	43504	1,848	39,711
CC6571D-30	Kubota®	Single	71 HP	Diesel	30"	5801163	54080	1,852	39,798
CC6571D-36	Kubota®	Single	71 HP	Diesel	36"	5801164	41741	1,855	39,964
CC6571D-42	Kubota®	Single	71 HP	Diesel	42"	5801165	55633	1,905	40,216
CC6571D-3-14	Kubota®	3-Speed (14"/26"/36")	71 HP	Diesel	14"	5801170	59044	1,815	44,625
CC6571D-3-20	Kubota®	3-Speed (20"/30"/42")	71 HP	Diesel	20"	5801171	55695	1,825	44,702
CC6571D-3-26	Kubota®	3-Speed (14"/26"/36")	71 HP	Diesel	26"	5801172	43503	1,835	44,782
CC6571D-3-30	Kubota®	3-Speed (20"/30"/42")	71 HP	Diesel	30"	5801173	55713	1,845	44,814
CC6571D-3-36	Kubota®	3-Speed (14"/26"/36")	71 HP	Diesel	36"	5801174	55728	1,850	44,968
CC6571D-3-42	Kubota®	3-Speed (20"/30"/42")	71 HP	Diesel	42"	5801175	55729	1,894	45,197

Horsepower and torque as rated by the engine manufacturer.

CC6571D SINGLE SPEED RPM

Blade Size	Blade RPM	Max Cut Depth
14"	2,700	4-1/2"
20"	2,400	7-1/2"
26"	1,950	10-1/2"
30"	1,700	11-3/4"
36"	1,400	14-3/4"
42"	1,200	17-3/4"

CC6571D 3-SPEED RPM

Blade Size	Blade RPM	Gear Setting High, Med, Low	Max Cut Depth
14"	2,700	H	3-3/4"
20"	2,550	H	6-3/4"
26"	1,775	M	9-3/4"
30"	1,675	M	11-3/4"
36"	1,175	L	14-3/4"
42"	1,100	L	17-3/4"

CC6571D OPTIONS

Description	Part #	Cat #	List Price
Water Safety Switch	6010522	67821	\$168
Water Pump (electric)	6011032	02506	505
Spot Light	6010112	02427	186
Lowering Speed Metering Valve	6010227	02480	296
Blade stacking kit-4-1/2" flange (for blades 1-1/2" apart) 20" Max.	6010630A	23186	932
Blade spacing kit-4-1/2" flange (for blades 2" apart) 20" Max.	6010631A	23187	982
Blade spacing kit-4-1/2" flange (for blades 4" apart) 20" Max.	6010632A	16558	1,160
14" Tapered Mount Blade Guard	6010950	20011	453
20" Tapered Mount Blade Guard	6010952	08213	673
26" Tapered Mount Blade Guard	6010954	19322	868
30" Tapered Mount Blade Guard	6010956	20456	1,071
36" Tapered Mount Blade Guard	6010958	13375	1,203
42" Tapered Mount Blade Guard	6010960	08216	1,359

