Husqvarna FS 309



Applications

- · Ideal for cutting in difficult to access job sites.
- · Utilized for very small road repair jobs.
- · A great rental saw, it is perfect for residential jobs.
- · Left-hand sawing only.

Benefits

- Very lightweight and compact, it eases transporting and handling of the saw.
- Adjustable handle and extendable right rear wheel increases stability and reduces fatigue.
- Gas assisted raise/lower system reduces the force required to raise and lower the blade in and out of the cut.
- Excellent power transmission to the blade due to the Poly V-belt, which increases production.

	FS 309
Item No.	967678301
List Price	\$1,974.00

Technical specifications

Maximum blade diameter, in (mm)	14 (350)
Maximum depth of cut, in (mm)	4-5/8 (117)
Average bladeshaft, rpm	3,500
Blade flanges, in (mm)	4-½ (114)
Maximum weight crated, lbs (kg)	198 (90)
Maximum weight uncrated, lbs (kg)	117 (53)

Specs for the FS 309

Power source	Robin EX27X	Wheels rear, in (mm)	6 x 1-½ x 5/8 (152 x 38 x 16)
Maximum power, hp (kW)*	8-1/2 (6)	Blade guard type	Bolt On
Power at bladeshaft, hp (kW)	N/A	Number of belts	14 rib poly V
Arbor size, in (mm)	1 (25)	Blade depth control	Screw feed
Bladeshaft diameter, in (mm)	3/4 (19)	Dimensions uncrated, pointer and blade guard up, handles in, in (mm) L x W x H	36 x 15 x 39 (915 x 381 x 990)
Cylinders/cycle	1/4		
Fuel capacity, gal (1)	1.6 (6.1)	Displacement, cu in (I)	16.2 (265)
Air filter	Dry type dual element cyclone	Bore/stroke, in (mm)	2.95 (75)/2.36 (60)
Starter	Recoil	Oil capacity, qt (I)	1.2 (1.1)
Engine cooling	Air	Handlebar adjustment	Variable Position
Axle front/rear, in (mm)		Transmission type	Push
Wheels front, in (mm)	4 x 1-½ x 5/8 (114 x 38 x 16)	*As rated by the engine manufacturer.	

RECOMMENDED DIAMOND TOOLS VARI-CUT™ PLUS