

Husqvarna FS 413

FLAT SAWS



Shown with optional water tank.

Applications

- Handles medium to small service work and repair jobs in concrete or asphalt. Perfect for rental.

Benefits

- A push saw with a clear focus on ergonomics, which reduces operator fatigue.
- Patented engine and bladeshaft mounting system reduces vibration for improved cutting performance.
- Patented IntelliSeal bladeshaft system allows for a minimum of 250 maintenance-free hours and eliminates daily greasing of bearings.
- The spring-assist screw feed adjustment feature reduces the force required to raise and lower the blade in and out of the cut.
- Compact and easy to transport.

FS 413	
Item No.	965150107
List Price	\$3,845.00

Technical specifications

Maximum blade diameter, in (mm)	20 (508)
Maximum depth of cut, in (mm)	7-5/8 (196)
Average bladeshaft, rpm	2,620
Blade flanges, in (mm)	4-1/2 (114)
Maximum weight crated, lbs (kg)	379 (172)
Maximum weight uncrated, lbs (kg)	306 (139)

Specs for the FS 413

Power source	Honda GX390	Wheels rear, in (mm)	8 x 2 x 5/8 (203 x 51 x 16)
Maximum power, hp (kW)*	11 (8)	Blade guard type	Slip-on with bolt
Arbor size, in (mm)	1 (25)	Number of belts	12 rib poly v belt
Bladeshaft diameter, in (mm)	1-3/16 (30)	Blade depth control	Spring assist screw feed
Cylinders/cycle	1/4	Dimensions uncrated, pointer and blade guard up, handles in, in (mm) L x W x H	59 x 25-3/4 x 41 (1,499 x 654 x 1,041)
Fuel capacity, gal (l)	1.6 (6.1)	Displacement, cu in (l)	23.7 (389)
Air filter	Dry type dual element cyclone	Bore/stroke, in (mm)	3.5 (88)/2.5 (64)
Starter	Recoil	Oil capacity, qt (l)	1.2 (1.3)
Engine cooling	Air	Handlebar adjustment	Variable Position
Axle front/rear, in (mm)	3/4 (19)	Transmission type	Push
Wheels front, in (mm)	4 x 1-1/2 x 5/8 (114 x 38 x 16)		

*As rated by the engine manufacturer.

RECOMMENDED DIAMOND TOOLS

VARI-CUT™ PLUS