

890 Series

The ICS 890 Series hydraulic cutting system offers the superior strength of FORCE4® technology. From the redesigned, more durable rear handle, to the easy to replace drive sprocket, this saw is engineered to stand up to your toughest jobs. The flush version cuts within 3/16" of a wall or floor. This package exceeds industry standards and this sleek powerhouse is packed with features designed to make it work as hard as you do.

890 SERIES PRODUCT SPECIFICATIONS

	8 GPM/30 LPM	12 GPM/30 LPM
Weight	27.3 lbs/24.3 kg with 15-in/38 cm bar/chain and 1' hose whips	
Bar length	up to 25 in/63 cm	
Motor Speed	6100 rpm	6500 rpm
Powerhead dimensions	23 in (58.5 cm) length 10.5 in (26.5 cm) height 9.5 in (24 cm) width	
Torque	122 in-lbs/13.8 Nm	170 in-lbs/19.2 Nm
Horsepower	11.5 hp/8.6 kW	17.5 hp/13 kW
Hydraulic Supply	8 gpm/30 lpm, 2500 psi/172.5 bar	12 gpm/45 lpm, 2500 psi/172.5 bar
Noise Level	98 dB @ 3 ft (1 m) (Sound pressure level) 107 dB @ 3 ft (1m) (Sound power level)	
Vibration Level	2.0 m/second ² (front handle) 6.0 m/second ² (rear handle)	
Water Supply	Minimum 20 psi (1.5 bar)	

• Product data shown is rated based on maximum input conditions and efficiency assumptions and may vary dependent on power supply.



ICS, BLOUNT INC. HEADQUARTERS | 4909 SE International Way Portland, OR 97222-4679 | PHONE 800.321.1240 · FAX 503.653.4393

© Copyright 2014-2015 ICS, Blount Inc. Privacy statement specifications subject to change without notice.

Pricing and specifications subject to change without notice. All rights reserved. ICS, WallWalker, SpeedHook, SealPRO, FORCE4 and PowerGrit are registered trademarks of ICS. The best way to cut concrete, DCT, TSS, ProFORCE and TwinMAX are trademarks of ICS.1214