





## Husqvarna K 760 Cut-n-Break

*Our Cut-n-Break method is the natural choice when you need to cut deep without overcutting at the corners. The K 760 Cut-n-Break enables you to cut as deep as 16" from one side. The two high-speed blades make a core in the saw cut, which can then easily be broken off using the accompanying breaking tool. This way you easily work your way through the material, at a very low diamond tool and maintenance cost. Delivered with twin blades and a breaking tool.*



### **COST-EFFICIENT CUTTING METHOD**

With the unique cut-n-break method you can work your way through the material step-by step at a low tool cost.



### **EXCEPTIONAL CUTTING DEPTH**

The long body and double cutting blades allow you to make cuts up to 16" deep.



### **HIGH PERFORMING BLADES INCLUDED**

Twin blades, with a very stable core and cutting performance are delivered with the machine.



### **OPTIMIZED ENGINE PERFORMANCE**

Optimized engine performance through efficient cylinder design, digital ignition system and X-Torq® engine technology.

## Features Husqvarna K 760 Cut-n-Break

- Easy to start
- Light and powerful
- The only time the filter needs to be checked and changed is if you experience lack of power.
- High power with less fuel
- Our X-Torq® engine produces less emissions, has lower fuel consumption and results in more power.
- Blade retarder
- Patented, dust sealed starter unit with a sealed return spring and pulley bearing. DuraStarter™ also includes a starter cord with greatly increased durability. This makes the starter virtually maintenance free, further enhancing the reliability of our cutters.
- Our virtually maintenance free starter, thanks to the dust-sealed starter and the durable starter cord.
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- Our built-in automatic filter compensation maintains high power during the air filter life time.
- The water adjustment gives efficient dust management and makes operation easier and more efficient.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.
- EasyStart ensures easier starting by reducing the compression in the cylinder.

### TECHNICAL SPECIFICATION

Engine	Air-cooled 2 stroke engine
Cylinder displacement	4.48 cu.inch
Power output	5 hp
Fuel tank volume	30.4 fl oz
Idling speed	2700 rpm
Vibrations front handle	1.9 m/s <sup>2</sup>
Vibrations rear handle	2.8 m/s <sup>2</sup>
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Blade diameter	9 inch
Max cutting depth	16 inch
Weight (excl. cutting equipment)	21.2 lbs
Weight incl. cutting equipment	24.5 lbs

