

STORE

SELF BUNDED TANK RANGE

SUITABLE FOR THE STORAGE & DISPENSING OF DIESEL, KEROSENE, LUBRICANTS, PETROL & WASTE OIL

- An innovative new range of Self Bunded Tanks available in 5,500L, 11,000L and 16,000L capacities.
- The STORE is perfect for home base refueling applications.
- The STORE features a weatherproof lockable full height pump bay housing for secure storage of dispensing equipment.
- Galvanised grated bunded area with drain.
- DN50 (2") Flanged 150# Fill Point with Full Bore Ball Valve / Non Return Valve / Male Camlock Fitting / Dust Cap / Mechanical Overfill Protection Valve and 12V Overfill Alarm.
- DN50 (2") Flanged 150# Suction Point with Anti Syphon / Foot Valve Assembly.
- Spare DN25 (1") Suction Outlet.
- Numerous spare fittings on top of the tank for retrofitting of instrumentation or other devices.
- 600mm dia manway with internal ladder.
- Calibrated anodised aluminium dipstick with brass lockable dip stick cover fitting.
- Anodised aluminium interstitial dipstick with brass lockable dip stick cover fitting.
- Interstitial emergency vent.
- Primary tank free air vent.
- Statutory safety decals.
- Raised base design to ensure full air circulation around the tank and provides access for forklift loading.
- Certified crane lifting lugs have been incorporated to facilitate crane loading and positioning on site. The lifting lugs are NOT certified to lift the tank with fuel.
- Letterbox style secure weatherproof hose inlet / outlet assembly.
- Paint Colour RAL9003 Signal White / Tanks are sandblasted to SA2 Standard. Hempel Marine Paint 3 Stage process. Primer Hempadur 1530. 2nd Coat Hempadur Hi-Build 4520. Final Coat Hempthane Enamel 55100 Finished dry film thickness no less than 180 um.



PRODUCT RANGE

	STORE-5.5	STORE-11	STORE-16
Capacity	5,500L	11,000L	16,000L
Safe Fill Level	5,000L	10,000L	15,000L
Length (mm)	2,950	2,950	3,950
Width (mm)	1,140	2,240	2,240
Height (mm)	2,520	2,520	2,520
Weight (kg)	1,850	3,075	3,550

