

## EXTERNAL DIMENSIONS

Length	1561mm
Width - Front	1574mm
Width - Rear	1688mm
Height	573mm
Weight	90kg

## STRUCTURE

Internal and External frame	Galvannealed steel – stamped 0.7-0.8mm
Reinforcement Sections	Galvannealed steel – stamped 0.7-1.2mm

## EXTERIOR ACCESSORIES

Front Window Type	Safety glass tempered with E-mark and AS2
Front Windows Feature	Non-tinted sliding glass
Front Window Thickness	4mm
Side Window Type	Safety glass tempered with E-mark and AS2
Side Window Feature	Tinted glass 60% dual lift window
Side Window Thickness	4mm
Rear Window Type	Safety glass tempered with E-mark and AS2
Rear Window Feature	Tinted glass 60%
Rear Door Demister	12v DC, 15a
Rear Door Thickness	4-5mm
Roof Rail Weight Capacity	100kg

## INTERIOR ACCESSORIES

Head Lining Insides	8mm foam
Head Lining Upper	Grey 0.5mm thick artificial leather vinyl
Head Lining Lower	Dark grey 0.8mm thick artificial leather vinyl
Room Lamp & Auto Switch	12v DC, 10w
Window Locks	Secure twin rotary door locks
Rear Door Lock System	2 point key and vehicle wired central locking
Rear Door Brake Light	LED E-mark 12v DC, 2.2w
Rear Door Gas Spring – Oil	Hydraulic oil shell clavus G32
Rear Door Gas Spring - Gas	Gas nitrogen

## INSTALLATION KIT

Mounting Clamp	Aluminium 4-point
Wiring Electrical Harness	Universal for central locking, demister, brake light etc.
Roof Rails	Aluminium, epoxy coated

## PAINT

Electrophoretic Deposition	"A" 40-50 µm
Top Coat	Colour-coded "A" 95-115 µm