

# Enviro STX

## Acrylic Polymer Additive



### DESCRIPTION

Enviro STX is an acrylic polymer additive, specifically formulated to be used with Enviro GTA and Enviro GTX to increase strength and flexibility, when adhering to Enviro 700X and Enviro HP1200.

### FEATURES

- High polymer content
- Increased adhesion
- Increased flexibility
- Low VOC content

### TYPICAL USES

Enviro STX can be used as an additive for Enviro GTX and Enviro GTA, when direct stick tiling to Enviro 700X and Enviro HP1200. Enviro STX can be used internally and externally, in the following areas:

- Bathrooms
- Laundries
- Kitchens
- Balconies
- Stairways

### PHYSICAL PROPERTIES

Appearance	White Liquid
Open Time	As per Enviro GTX and GTA
Dry Time	As per Enviro GTX and GTA
Pot life	As per Enviro GTX and GTA
Mix ratio	500ml per bag of adhesive

### SUBSTRATE PREPARATION

When tiling over non-sand seeded 700X, use Enviro STX at a min rate of 500ml per bag of Enviro GTX tile adhesive. This can be increased to 1lt if extra adhesion is required. No priming is required.

When tiling over Enviro HP1200 use Enviro STX at a min rate of 500ml per bag of Enviro GTX tile adhesive. This can be increased to 1lt if extra adhesion is required. Priming is required, refer to Enviro GTX datasheet for further information.

For further information on substrate preparation or for project specific advice, please consult EnviroSystems.

[customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)

### MIXING

Add Enviro STX to water at a min rate of 500ml per kit, and up to 1lt if extra adhesion is required. The required water content for the tile adhesive should be adjusted, accounting for the inclusion of Enviro STX.

### COVERAGE

The consumption of Enviro STX will depend on the required level of adhesion.

Typically, between 500ml and 1 litre of Enviro STX, is used per bag of Enviro Tile Adhesive.

### PACKAGING & COLOURS

Enviro STX is supplied in 1 litre and 5 litre pails.



## CLEANING

Excess Enviro STX can be cleaned using a damp cloth. Tools can be cleaned up with water prior to curing. Cured material must be mechanically removed.

## SHELF LIFE

Enviro STX can be stored in its original sealed containers for 12 months, when placed in a cool, dry environment. Once opened and resealed for later use, the shelf life could vary depending on storage conditions. Always check product quality before using after prolonged periods of storage. If unsure please contact EnviroSystems for advice.

## HEALTH & SAFETY ADVICE

Refer to the Safety Data Sheet for full safety and handling procedures.

**NOTE:** Safety Data Sheets are available upon request by emailing [customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)

## We're here to help you!

It is a good idea to keep a journal of your waterproofing job, whether big or small.

- Take pictures at all stages of your work, including preparation
- Record the quantity and description of products used with corresponding batch numbers
- Record dates and times of when you applied products, from start to finish

Please do not hesitate to contact us for any questions you may have.

EnviroSystems Technologies Pty Ltd

**Address** 295 Princes Highway, St Peters NSW 2044  
Sydney, Australia  
**Phone** +61 2 8595 8699  
**Fax** +61 2 8595 8660  
**Email** [customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)  
**Web** [www.envirosystems.com.au](http://www.envirosystems.com.au)



## STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use of application and no warranty as to accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use. Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by EnviroSystems Technologies either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not EnviroSystems Technologies are responsible for carrying out procedures appropriate to a specific application.