RESPIRATORY GEAR

P2 DISPOSABLE RESPIRATOR WITH EXHALATION VALVE

PRODUCT DATA SHEET: PC321 | PC321-3 | PC321-20



PRODUCT CODE:



PRODUCT CODE:













FEATURES AND BENEFITS

- P2 Certified to AS/NZS 1716:2012 Respiratory protective devices.
- P2 disposable respirator for protection against mechanically and thermally generated particles.
- Lightweight cupped design for comfortable extended wear.
- Dual latex free elastic straps for ease of donning and doffing.
- ProValve exhalation valve for decreased breathing resistance and
- Nose flange for increased protection and facial fit.
- Resealable bag for hygienic storage.

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
PC321	PACK	1	30
PC321-3	BOX	1	20
PC321-20	BOX	1	20

PRODUCT DETAILS

Latex-free rubber band Straps: Filter Media: Polypropylene melt-blown

Weight: 14g +- 5g each Nose Flange: PU foam

CAREINSTRUCTIONS

Shelf life of the unopened product is three (3) years from date of manufacture when stored within the temperature range of -5°C to +50°C and less than 80% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Ensure disposable mask is correctly fitted prior to each use and conduct annual fit testing in accordance with AS/NZS 1715:2009.













WARNINGS AND USE LIMITATIONS

- 1. Facial hair has the potential to compromise the required protective seal of the respirator.
- 2. Ensure adequate oxygen levels are present.
- 3. Ensure the contamination is known and the respirator is suitable for the application.
- 4. Replace when taste, smell or the breathing resistance is high.
- 5. Store in a clean resealable storage device.

STANDARDS

CERTIFIED TO:

AS/NZS 1716:2012 Respiratory Protective Devices. Certified by Benchmark - Identification number: BMP547903



To be used in conjunction with:

AS/NZS 1715:2009 Selection, use and maintenance of respiratory protective equipment.

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES	
P1	80% (Particles to 1μm micron = 0.001mm size)	Dust	
P2	94% (particles to 0.3μm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes	
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only	



12 FELLOWSHIP ROAD. GNANGARA, WA 6077 TECH SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

