# **Safety Data Sheet**

# **ULTRALITE S2 T FLEX GREY**

Safety Data Sheet dated: 16/02/2022 - version 2

Date of first edition: 14/01/2022



#### 1. Identification

#### **GHS Product identifier**

Mixture identification:

Trade name: ULTRALITE S2 T FLEX GREY

Trade code: 9011967

#### Recommended use of the chemical and restrictions on use

Recommended use: no data available Uses advised against: no data available

Supplier's details

Company: MAPEI AUSTRALIA Pty Ltd

180 Viking Drive Wacol QLD 4076 Australia

T. +61 7 32765000 (Mon-Fri 8am to 4.30pm)

F. +61 7 32765076

Responsible: sales@mapei.com.au

Emergency phone number

Australian Poisons Information Centre 24 Hour Service 13 11 26

Police or Fire Brigade 000

#### 2. Hazard identification





### **Classification of the Hazardous chemical**

Skin Irrit. 2 Causes skin irritation.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1B May cause an allergic skin reaction.

STOT SE 3 May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

### GHS label elements, including precautionary statements

# **Pictograms and Signal Words**



Danger

#### **Hazard statements:**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.H335 May cause respiratory irritation.

# **Precautionary statements:**

P261 Avoid breathing dust.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P321 Specific treatment (see supplementary instructions on this label)
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Date 2/16/2022 Production Name ULTRALITE S2 T FLEX GREY Page n. 1 of 9

P362 Take off contaminated clothing and wash before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with applicable regulations.

#### Other hazards which do not result in a classification

Other Hazards: No other hazards

### 3. Composition/information on ingredients

#### Substances

no data available

**Mixtures** 

Mixture identification: ULTRALITE S2 T FLEX GREY

# Hazardous components within the meaning of the "Australian Work Health and Safety (WHS)" regulation and related classification:

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
≥50 - <75 %	Portland cement, Cr(VI) < 2 ppm	CAS:65997-15-1 EC:266-043-4	Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Dam. 1, H318; STOT SE 3, H335	
≥10 - <20 %	free crystalline silica (Ø >10 $\mu$ )	CAS:14808-60-7 EC:238-878-4		
≥10 - <20 %	Calcium carbonate	CAS:471-34-1 EC:207-439-9		Exempted
≥1 - <2.5 %	Calcium diformate	CAS:544-17-2 EC:208-863-7	Eye Dam. 1, H318	

#### 4. First-aid measures

#### **Description of necessary first-aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

#### Symptoms caused by exposure

Eye irritation

Eye damages

Skin Irritation

Erythema

### Medical attention and special treatment

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

### 5. Fire-fighting measures

### Suitable extinguishing media

None in particular.

Water.

Carbon dioxide (CO2).

# Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: no data available

Explosive properties: no data available

Date 2/16/2022 Production Name ULTRALITE S2 T FLEX GREY Page n. 2 of 9

Oxidizing properties: no data available

### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

#### **Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

#### Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations

Scoop into containers and seal for disposal.

Retain contaminated washing water and dispose it.

### 7. Handling and storage

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

# 8. Exposure controls/personal protection

# Control parameters – exposure standards, biological monitoring

National UNITED

**KINGDOM** 

# List of components with OEL value

List of components with	II OLL V	iiue							
Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
Portland cement, Cr(VI) < 2 ppm	Nationa	I FINLAND		1					FINLAND, respirabel fraktion
	AUS			10.000					10 mg/m3 PEL
	Nationa	I SPAIN		4.000					5 mg/m3 TWA (containing <1% of free Silica, respirable dust);10 mg/m3 TWA (containing <1% of free Silica, total dust)
	Nationa	I PORTUGAL		10					
	Nationa	I BELGIUM		10					
	Nationa	I HUNGARY		10					
	Nationa	l UNITED KINGDOM		10.000					inhalable dust
		_							

Date 2/16/2022 Production Name ULTRALITE S2 T FLEX GREY Page n. 3 of 9

respirable dust

4.000

	National	CROATIA	10.000	10.000	
				10.000	A4 Not Classifiable as a
	ACGIH	AUSTRALIA	1.000		A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma
	National	UNITED KINGDOM	10	30.000	5 mg/m3 TWA (containing <1% of free Silica, respirable dust);10 mg/m3 TWA (containing <1% of free Silica, total dust)
	National	UNITED KINGDOM	4.000		
	National	ROMANIA	10		
	National	CROATIA	4.000	10	
	OSHA		15		
	OSHA		5		
	ACGIH		1		A4 - Not Classifiable as a Human Carcinogen; pulmonary function; respiratory symptoms; asthma
	AUS	AUSTRALIA	10		
	National	SPAIN	4		
	National	FINLAND	5		
	National	FINLAND	1		
	National	PORTUGAL	1		
	National	BELGIUM	1		
	National	LATVIA	6		
	National	UNITED KINGDOM	10	30	
	National	UNITED KINGDOM	10	12	
	National	UNITED KINGDOM	4	30	
	National	CROATIA	10		
		CROATIA	4		
free crystalline silica (Ø $>10 \mu$ )		DENMARK	0.3		DENMARK, inhalable aerosol
	National	DENMARK	0.100		DENMARK, respirable aerosol
	National	SWITZERLAND	0.15		A
	ACGIH	None	0.025		(R), A2 - Pulm fibrosis, lung cancer
	National	NORWAY	0.300		K: Chemicals to be treated as carcinogenic.
	National	AUSTRALIA	0.050		
	ACGIH		0.025		A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	National	FRANCE	0.100		
	National	SPAIN	0.050		
	National	FINLAND	0.05		
	National	PORTUGAL	0.025		
		BELGIUM	0.100		
	National	CZECH REPUBLIC	0.100		

Date 2/16/2022 Production Name ULTRALITE S2 T FLEX GREY Page n. 4 of 9

National HUNG	ARY	0.150	
National DENM	ARK	0.300	
National DENM	ARK	0.100	
National SWED	EN	0.100	
National ESTO	AIV	0.100	
National SLOV	AKIA	0.100	0.500
National SLOVE	ENIA	0.1	
National BULG	ARIA	0.070	
National LITHU	IANIA	0.100	
National ROMA	NIA	0.100	
National CROA	TIA	0.100	
AUS AUSTI	RALIA	10	
National FRANC	CE	10	
National PORT	JGAL	10	
National LATVI	A	6	

### **Predicted No Effect Concentration (PNEC) values**

Component	CAS-No.	PNEC Limit	Exposure Route	<b>Exposure Frequency Remark</b>
Calcium carbonate	471-34-1	100 mg/l	Microorganisms in sewage treatments	

### **Derived No Effect Level. (DNEL)**

Component	CAS-No.	Worker Work Industr Profe y ional		Exposure Route	Exposure Frequency Remark
Calcium carbonate	471-34-1	6.36 mg/m3	1.06 mg/m3	Human Inhalation	Long Term, local effects
			6.1 mg/kg	Human Oral	Long Term, systemic effects
			6.1 mg/kg	Human Oral	Short Term, systemic effects

### **Appropriate engineering controls**

no data available

Calcium carbonate

# Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; AS/NZS 2161.10:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

### Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to AS/NZS 1715-1716 for information on selection and use of appropriate respiratory protection equipment.

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

# 9. Physical and chemical properties

Physical state Solid

Color Grey

Appearance: powder Odour: cement like

Odour threshold: no data available

pH:

pH (water dispersion, 10%): 12.00

Melting point / freezing point: no data available

Date 2/16/2022 Production Name ULTRALITE S2 T FLEX GREY Page n. 5 of 9

Initial boiling point and boiling range: no data available

Flash point: no data available Evaporation rate: no data available

Flammability (Solid, Gas): no data available

Upper/lower flammability or explosive limits: no data available

Vapour pressure: no data available Vapour density: no data available Relative density: no data available Solubility in water: no data available Solubility in oil: no data available

Partition coefficient (n-octanol/water): no data available

Auto-ignition temperature: no data available Decomposition temperature: no data available

Viscosity: no data available

Specific heat value: no data available

Saturated vapour concentration: no data available

Release of invisible flammable vapours and gases: no data available

Particle size: no data available

Particle size distribution: no data available Shape and aspect ratio: no data available

Crystallinity: no data available Dustiness: no data available

Specific surface area: no data available

Degree of aggregation or agglomeration, and dispersibility: no data available

Biodurability or biopersistence: no data available Surface coating or chemistry: no data available

VOC % (Volatile Organic Compound): 10 (Rule 1168) g/l

# 10. Stability and reactivity

#### Reactivity

Stable under normal conditions

# **Chemical stability**

no data available

# Possibility of hazardous reactions

None.

# **Conditions to avoid**

Stable under normal conditions.

# **Incompatible materials**

None in particular.

# Hazardous decomposition products

None.

# **SECTION 11: Toxicological information**

# Information on toxicological effects

# Toxicological information on main components of the mixture:

free crystalline silica (Ø  $>10 \mu$ )

a) acute toxicity

LD50 Oral > 2000 mg/kg

LD50 Skin > 2000 mg/kg

Calcium carbonate

a) acute toxicity

LD50 Oral Rat > 2000 mg/kg LC50 Inhalation Rat > 3 mg/l

LD50 Skin Rat > 2000 mg/kg 4h LD50 Oral Rat = 6450 mg/kg

g) reproductive toxicity

NOAEL Rat = 1000 mg/kg

Calcium diformate

a) acute toxicity

LD50 Oral Rat = 2650 mg/kg

Date 2/16/2022 Production Name ULTRALITE S2 T FLEX GREY Page n. 6 of 9

# 12. Ecological information

#### **Ecotoxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

# List of components with eco-toxicological properties

Component Ident. Numb. Ecotox Infos

Calcium carbonate CAS: 471-34-1 - c) Bacteria toxicity: NOEC Bacteria = 1000 mg/L 3

EINECS: 207-439-9

d) Terrestrial toxicity: LC50 > 1000 mg/kg

d) Terrestrial toxicity : NOEC = 1000 mg/kg - 28 d

e) Plant toxicity: NOEC = 1000 mg/kg - 21 d

Calcium diformate CAS: 544-17-2 - a) Aquatic acute toxicity: LC50 Fish Brachydanio rerio >= 1000 mg/L 96h

EINECS: 208-863-7 IUCLID

### Persistence and degradability

no data available

#### **Bioaccumulative potential**

no data available

#### Mobility in soil

no data available

#### Other adverse effects

no data available

#### 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

### Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

### Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

# 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

#### **UN** number

no data available

### **UN proper shipping name**

no data available

# Transport hazard class(es)

no data available

# Packing group, if applicable

no data available

#### **Environmental hazards**

no data available

#### Special precautions for user

no data available

# **Additional Information**

no data available

Date 2/16/2022 Production Name ULTRALITE S2 T FLEX GREY Page n. 7 of 9

no data available

# 15. Regulatory information

### Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Australian Work Health and Safety (WHS) act and the Code of Practice on preparation of safety data sheets for Hazardous Chemicals.

AICS: all components are listed

#### 16. Other information

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

Date 2/16/2022 Production Name ULTRALITE S2 T FLEX GREY Page n. 8 of 9

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

# Paragraphs modified from the previous revision:

- 9. PHYSICAL AND CHEMICAL PROPERTIES

Date 2/16/2022 Production Name ULTRALITE S2 T FLEX GREY Page n. 9 of 9