

Stress Grading Ink [WB800]



Dy-Mark's WB800 Stress Grading Inks are lightfast timber branding inks that are used for the identification of stress graded timber. Stress Grading Ink is suitable for use with automatic stress grading machines and green chain branders.

DIRECTIONS FOR USE

Application

Timber Stress Grading Ink needs to be diluted with water prior to use. Dilution rates are as follows:

Black: 1:2

Green: 1:15 to 1:20

Red: 1:15 to 1:20

Violet: 1:15 to 1:20

TECHNICAL DATA

Size:	10 litre, 20 litre
Colour:	Invisible Blue, Black, Red, Blue, Green, Orange, Violet, Grey
Consistency:	Liquid
Suitable Surfaces:	Timber
Drying Time:	10 minutes
Clean Up:	Water

STORAGE

Store below 50°C.

DISPOSAL

Allow left over paint to dry and dispose of this residue in your normal rubbish. Dispose of container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

SAFETY INFORMATION

NON-FLAMMABLE

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.