PASSIVE FIRE PROTECTION

PHONE: (07) 5411 4209

OR (02) 8004 3333 (Option 2)

WEBSITE: tbafirefly.com.au

EMAIL: sales@tbafirefly.com.au

MATERIAL DESCRIPTION

TBA Firefly Phoenix EA Sarking is a lightweight, waterproof sarking, foil faced on one side.

CERTIFICATION

AS1530.1 Non-Combustibility CSIRO Report No: FNC11220

AS1530.4

BRANZ Report Number FAR2701 (Vertical Only)

AS1530.2-1993 Flammability Test AWTA Report Number 7-576926-CN

AS4200.1-1994 Clause 6.1.3

AS1301.448s -1991

AS/NZS 4200.1-1994 Table 1 (Extra Heavy Duty)

Number: 7-577747-CN AS/NZS4201.4-1994 (PASS)

AS/NZS4200.1-1994 CLAUSE 6-4 (High)

AWTA Report

Full compliance to AS3959-2009 Extra Heavy

DIMENSIONS

ROLL

 $25m \times 1m = 25m^2$ 1 mm Thick 560g per m²

FRL -/90/-

APPLICATIONS

Phoenix EA extra heavy duty sarking is used to wrap the outside of timber or steel roof and wall frames to provide superior protection against mild to severe ember attack during bush fires. In addition to it's flammability index of 1 it has a Fire Rating Level of -/90/- when tested to AS1530.4 (Method for fire tests on building materials, components and structures).





