

**PHONE:** (07) 5411 4209  
**OR** (02) 8004 3333 (Option 2)

**WEBSITE:** [tbafirefly.com.au](http://tbafirefly.com.au)  
**EMAIL:** [sales@tbafirefly.com.au](mailto:sales@tbafirefly.com.au)

## MATERIAL DESCRIPTION

TBA Firefly™ Aluminium Foil Reinforced Tape is comprised of fire-retardant acrylic adhesive and two non-combustible layers. A Fortaglas reinforcement layer and an aluminium foil layer.

## CERTIFICATION

Tested and approved to NCC 2019 Volume 1  
(Amendment 1)  
Clause C1.9 Non-combustible Building Elements  
Report: CSIRO FCO-3289

Tested in accordance with  
AS/NZS 1530.3-1999  
The Spread-of-Flame Index and the  
Smoke-Developed Index of the composite panel  
did not exceed 0 and 2 respectively.

AS 1530.1-1994  
Both layers are NOT deemed COMBUSTIBLE

## DIMENSIONS

75mm Wide x 50M Long Roll

## APPLICATIONS

TBA Firefly™ Aluminium Foil Reinforced Tape is used for sealing our TBA Firefly™ Non-Combustible Sarking joints.

**TBA FIREFLY™  
ALUMINIUM FOIL REINFORCED TAPE**



TBA Firefly™  
Aluminium Foil Reinforced Tape



TBA Firefly™ Aluminium Foil Reinforced Tape  
Installed onto the Joints of the  
TBA Firefly™ Non-Combustible Sarking