







# **PRODUCT DESCRIPTION:**

RLA Carpet Latex is a compounded latex product used for the sealing of raw edges, strengthening worn backing, replacing damaged nap and adhering pad underlays to Subfloors.

# FOR BONDING:

**Domestic Underlays:** 

Apply a liberal amount latex to a dry, clean, sound and smooth substrate. Place underlay into the wet latex install underlay in accordance to manufactures recommendations.

#### Sealing Selvedge:

Prior to Heat Bond Seaming, most tufted and woven carpets are prone to lose tufts or unravel after the selvedge is trimmed. It is recommended Carpet Latex be applied to the edge of the seam prior to Head Bond Seaming. Work latex into the edge and allow to dry before seaming.

#### Worn Backing:

Lay carpet face down. Apply a liberal amount of latex to the carpet backing with a brush or roller to the areas that need attention to ensure a good bond. Allow the carpet to dry in position for 4-5 hours.

### **CLEAN UP:**

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using a suitable cleaning solvent applied to a damp cloth then rubbed gently over the dried adhesive or alternatively please use AFTEK Handy Wipes.

### **CONTAINER SIZES:**

5 litre plastic containers

# **SHELF LIFE / STORAGE:**

12 months when stored in original unopened packaging To be stored in a dry area off the ground.

### **SAFETY & HANDLING**

A Safety Data Sheet is available on request. Product is classified as NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.







### Warranty Statement:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that when fully cured this product is suitable for use and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace product free of charge when purchased from any legally verifiable source, and where product is proven to have been stored, handled and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with the relevant Australian Standard and the Floorcovering Manufacturers instructions and the floorcoverings must have been subject to normal traffic conditions. Warranty doesn't not apply if damage, loss, failure to follow instructions or other circumstances are out of our control. Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

Phone: 1800 242 931

Email: info@rlapolymers.com.au

Mail: 215 Colchester Road Kilsyth Victoria 3137 (attention Customer Service)

### **Australian Consumer Law**

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

### Disclaimer

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Issued: January 2021

