

TANALISED® Enseal Clear

Treated Pine 'Cut End' Sealer

APVMA Registration No. 60012



TECHNICAL DATA SHEET
November 2011

1.0 DESCRIPTION

FORM:	White spirits based solution in a pressurised container.
CONTENTS:	26 g/kg (20 g/L) zinc (Zn) present as zinc naphthenate. 1.3 g/kg (1 g/L) permethrin 880 g/kg liquid hydrocarbons
PROPELLANT:	Hydrocarbon

2.0 FUNCTION

Enseal Clear is a transparent resealing solution intended for use on pressure treated timber in above ground applications where cutting, notching, drilling, machining or other work exposes areas of unpenetrated wood. This product is only for supplementary application to timber that has been preservative treated in accordance with AS1604. This product is not suitable for application to or protection of untreated timber.

3.0 DIRECTIONS FOR USE

For resealing of treated timber products where cutting to length, rebating, notching, drilling or other work during installation or fitting exposes fresh timber surfaces. Enseal Clear is suitable for timber surfaces that are above ground as in H2 and H3 situations as defined in AS1604. Do not place the resealed timber end or surface in ground contact.

Ensure adequate ventilation during use and avoid inhaling spray mist. Shake can briefly before use. The timber surfaces to be sprayed should be dry and clean. Turn spray tip so that the arrow on the nozzle points towards the surface to be sprayed. Hold can 15 to 20 cm from the surface. Apply the product liberally onto the freshly exposed surface until the solution ceases to absorb readily and just starts to run on the surface. Coverage should be up to 2 m² per can depending on wood condition and grain orientation (end grain will be most absorbent). Allow 2 days drying time before applying primer, paint or other sealants on the resealed timber surface.

This product is only for supplementary use on treated wood products that have been preservative treated in accordance with AS1604.

Do not use for any other purpose. Use of this or an equivalent product is recommended in order to conform with manufacturers guarantees on treated wood products.

4.0 STORAGE

PRESSURISED DISPENSER. Store in a cool, secure place. Protect from sunlight and do not expose to temperatures exceeding 50° C. Keep out of reach of children.

Enseal Clear is best used within 12 months from date of manufacture when stored in the above conditions in the original unopened container.

5.0 SAFETY & HANDLING

CAUTION: EXTREMELY FLAMMABLE

Do not store or use near fire or flame.
Do not spray on any incandescent material.
Keep away from sources of ignition.
Keep out of reach of children.
Do not smoke during use.
Use only with adequate ventilation.
Avoid inhaling spray mist.
Do not spray directly on humans, pets, food, food preparation surfaces or food utensils.
Wash hands after use.

WARNING: INTENTIONAL MISUSE BY DELIBERATELY INHALING OR SNIFFING THE CONTENTS MAY BE HARMFUL OR FATAL.

6.0 FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre immediately.
Phone 131 126

7.0 PACKAGING

Pressure cans: 300 g net contents

8.0 DISPOSAL OF EMPTY CONTAINERS

Do not pierce or burn, even after use. Recyclable steel – recycle used cans if a facility is available or place used cans in household rubbish.

See Material Safety Data Sheet for further information.

