



## PACER F75 SUBFRAME BLACK AEROSOL

### PRODUCT DESCRIPTION:

Pacer F75 Subframe Black is a quick drying, semi-gloss all-purpose rust and chip resistant epoxy based paint.

**APPLICATION:** Designed for painting subframes, chassis, radiators, automotive components, engine bays and most surfaces requiring a rust and chip resistant finish.

**SURFACE PREPARATION:** Remove all loose and flaking paint, build up of dirt and grime with a wire brush or coarse sand. Remove any loose rust and then treat residual rust and bare metal with a compatible rust remover Sand existing paint with P400 paper and wash with Pacer P08Wax & Grease Remover to remove remaining contaminants on the surface. Mask off surrounding areas to avoid overspray.

**DIRECTIONS:** Shake can vigorously for 1 minute. Spray from a distance of approximately 25cm in an even sweeping motion. Apply several light coats to build up thickness gradually. Avoid applying a heavy coat which may cause runs to appear. Turn the can upside down and spray briefly to clear the nozzle after use.

**DRYING TIME:** 15 minutes to touch dry and 24 hours to hard dry.

**CLEAN UP:** Use Pacer F59 Enamel Thinner.

**STORAGE:** Store upright in a cool, dry, well ventilated area away from heat, ignition sources and direct sunlight. Always replace lid securely after use

**PACK SIZE:** 400g

**HEALTH & SAFETY:** Safety Data Sheet is available at [www.cwbrands.com.au](http://www.cwbrands.com.au)

**Highly flammable**, do not use near fire or open flame. **Keep Out Of Reach Of Children.** If swallowed seek medical advice immediately or contact the **Poisons Information Center on 131126.**

**Spills and leaks:** Should be contained with absorbent material such as sand, earth or saw dust.

**Warning:** Intentional misuse by deliberately inhaling contents can be harmful or fatal. Do not puncture this container even when empty. Avoid breathing of vapour and mist. Provide adequate ventilation when spraying in confined spaces. Avoid contact with eyes and skin.

**DISPOSAL:** Aerosols should be completely empty before disposing. Dispose of in accordance with local, state and federal regulations.





## PACER F75 SUBFRAME BLACK AEROSOL

### Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure suitability of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.