



GSA POWDER FILLER

Description

GSA interior Powder filler is a fine particle filler suitable for filling patching holes and cracks and chips in most interior surfaces. It has minimal shrinkage, excellent adhesion and is easy to sand.

Applications: Ideal for filling small holes, cracks and chips, Suitable for repairs to plasterboard, plaster, masonry and most interior substrates.

Preparation: Surfaces should be clean and dry with no loose powdery material or paint. Prime any exposed metal prior to filling to reduce the chances of corrosion (nail holes etc.)

Application

- Mix up enough paste for your requirements that can be applied within 60 mins. GSA powder filler has a 45-60 minute working time when mixed according to instructions, depending on atmospheric conditions. **DO NOT ADD WATER TO EXTEND MIXED PRODUCT**
- Working time will be shortened at higher temperatures.
- Mix 3 parts powder to 1 part water in a clean container, this should be a toothpaste consistency. For deeper filling applications, a slightly stiffer consistency will aid workability and reduce drying time.
- Scrape a small amount of filler onto a flexible filling blade. Apply thin layers pressing firmly into the area being filled. Slightly overfill the surface to allow for the surface to be sanded smooth. Allow each layer to dry before applying next layer.
- Remove any excess filler by smoothing with a blade before filler dries.
- For optimum results, allow 24 hours for product to harden fully prior to sealing the surface.
- When dry, sand lightly (120-240 grit sandpaper) for an excellent surface for painting.

Specification

Tooling Time: 45-60 minutes

Cure time: 5-6 hours

Ready for painting : 24 hours

Packaging: 454-gram carton, 1.8 kg carton, 6 kg tub

Storage: Store in a cool dry place in a sealed container out of direct sunlight.

Limitations: Only suitable for interior use. Not suitable for joints where movement occurs use GSA gap

Health & Safety: Non-hazardous product. Keep away from children and animals. Do not take internally, keep out of eyes. If contact with skin, wash with soap and water.

First Aid

Please refer to the Safety Data sheet which is available at www.cwbrands.com.au/





GSA POWDER FILLER

Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.