



GSA Timber Filler

Description

GSA Timber Filler is a ready to use filler for interior use. It is suitable for filling holes and cracks in joinery and doors and can also be used as a grain and edge filler where a smooth surface is required.

Recommended Uses

- Ideal for filling hole, cracks, dents and chips in timber.
- Grain and edge filling.
- Interior joinery and doors.
- Can be stained or painted

Preparation: Ensure all surfaces are clean, dry and free from dust and grease. Remove all loose and flaking materials (including old filler) from the areas to be filled.

Application: Apply a small amount of filler onto a flexible filling blade. Apply in thin layers, pressing firmly into the area being filled, and remove any excess filler. Allow each area to dry before applying the next layer. Dries in 2-3 hours in thin applications, depending on atmospheric conditions. When dry, sand with 120-180 grit sandpaper to a smooth finish. GSA Interior Timber Filler can be primed with water or oil-based primer prior to top coating. When using tints and stains, the final application of clear varnish will deepen the colour of GSA Interior Timber Filler.

Clean Up: Clean tools and hands with warm soapy water.

Storage: 12 months in unopened container. Close lid tightly after use. Store in a cool place out of direct sunlight. To store filler after use, squeeze air from tube before recapping.

Packaging: TF2 – 200ml, TF75 – 750ml

Handy Tips for the Best Results: Deeper cavities should be filled in layers and allowed to dry to avoid cracking. GSA Fillers can be coloured with standard paint tinters.

First Aid: Please refer to the Safety Data Sheet which is available at www.cwbrands.com.au/

Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.

