



## Anchor High Temp Paint

**ANCHOR HIGH TEMP** is a premium quality, heat resistant paint that withstands temperatures of up to 600°C. Ideal for automotive exhaust manifolds, mufflers, BBQ's, grills, boilers, heaters, or any surface that becomes excessively hot. No primer required.

### PREPARATION:

Thoroughly clean the surface and ensure it is free from grease, oil, dirt, rust, scale, and other contaminants.

Lightly sand previously painted and glossy surfaces.

Wipe surface with mineral turps and allow to dry before painting.

Cover all necessary areas to protect from overspray.

### APPLICATION:

Before spraying:

Shake can vigorously for 1 minute to ensure colour uniformity. Shake can occasionally during use.

Remove the cap carefully. Avoid using sharp objects that may puncture the can.

Test spray on a small inconspicuous area to ensure surface compatibility and finish suitability.

### SPRAYING:

Select the nozzle setting.

Hold the can upright approximately 25cm from the surface.

Press button firmly and spray several light coats with a smooth sweeping motion, overlapping each spray pass. To prevent paint from sagging, avoid spraying too close to the surface or applying a heavy coat.

Repeat if necessary.

Do not use when air or surface temperature is below 15°C or above 30°C or in excessive humidity.

**COVERAGE:** Approximately 1.5m per can, depending on the nature of the surface and amount of overspray.

**DRYING:** Touch dry in 15 minutes. Re-coat after 1 hour. Drying will be slower in cold or humid conditions, in the absence of ventilation or where heavy film builds are applied. Hard dry conditions can be achieved when the coated article is heated.

**CLEAN UP:** Overspray can be removed while still wet with mineral turps. To clean the nozzle after use and prevent blocking, turn the can upside down and press button until only gas escapes.

### Packaging

300 gram aerosol can and 500 ml tin (matt Black only)

12 units per carton

1152 units per pallet





## Anchor Bond Spray Paint

### Storage/Shelf Life

Store in a cool place out of the sun. Do not store above 50°C.

### Health & Safety

Aerosols should be completely empty before disposing. Recycle empty can if facility is available. Ensure adequate ventilation when using in enclosed areas. Keep away from heat, flames or sources of ignition.

### Limitations

Avoid applying at temperatures below 10°C or in damp conditions. When applying at temperatures above 30°C, do a test spray to ensure the desired finish is achieved.

### Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage.