

**VITAL TECHNICAL SDN. BHD.****Technical Data Sheet****VT-760125 / VT-760250 / VT-760OV
Wood & Parquet Adhesive**

Issuance date: 26/02/2019

Revision date: 02/06/21

Revision No.: 21-0

Product Specification:

Appearance	: Viscous liquid
Color	: White
Viscosity (Brookfield LV 4 @ 5rpm)	: 20,000 – 35,000 cps
Specific Gravity	: 1.21 - 1.23 g/mL
Solid content	: 39.00 % - 41.00 %
Wet tack	: Aggressive
Flammability	: Non-flammable
Shelf life	: 24 months
Features	: Economical : Excellent adhesion : Easy clean up : Non-toxic

Packaging

Product Code	Content	Inner Box	Carton
VT-760125	125 g bottle	12	144
VT-760250	250 g bottle	12	72
VT-760OV	500 g bottle	-	24



VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

VT-760150

(Scan to learn how to use)



Visit product page:

<https://vitaltechnical.com/product/vt-760150-wood-and-parquet-adhesive/>**Product Description:**

A water-based adhesive that is excellent for wood bonding application. It features quick setting, superior bonding strength and it bonds variety of porous substrates.

Applications:

Suitable for parquet flooring installation and repair, wood joining, PVC lamination, furniture repair, wooden frames, woodworking projects, etc. **NOTE:** not for outdoor use

Directions:

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Apply the adhesive on both surfaces if the material is porous. Press together firmly and leave to dry.
3. Replace cap after use and store in a cool, dry place.

Caution:

Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Storage:

Minimum of 24 months in tightly closed packing when stored in cool and dry place, below 30 °C.

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- END -