

ENDCHECK

USES

Ideal for control of moisture in timber to prevent splitting. Suitable for application to drying timber to reduce the incidence of checks during the drying process.

Timber coated with Endcheck may not be suitable for the application of any paint or coating.

ADVANTAGES

- Easy and ready to use
- Can be diluted with water
- Applied by brush roller or spray
- Can be pigmented to identify application areas

PROPERTIES

Appearance	Milky like liquid
Solids content	46%
Specific gravity	.96 at 15°C
Odour	Low

APPLICATION INSTRUCTIONS

- Apply directly to timber surface by brush roller or knapsack spray
- Apply to freshly sawn logs or timber before air drying or kiln drying
- Clean up equipment with water
- Apply at a rate of 4 – 6m² per litre

STORAGE

12 months in original containers in a cool dry place

PACKAGING

20 Litre and 200 Litre drums

PRECAUTIONS

Health & Safety

ENDCHECK is non-toxic. However, ensure adequate protection and safety measures are maintained during application to prevent eye and skin contact. Prevent inhaling fumes and do not swallow.

NOTE

Material Safety Data Sheet is available on request. Read the MSDS and product label carefully before use.

All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

ALLIED PRODUCTS

Aftek manufactures a broad range of construction products including:

- Grouts
- Coatings
- Admixtures
- Adhesives
- Sealants
- Floor Toppings
- Floor Levelling Compounds
- Concrete Repair
- Concrete Treatment

The information and any recommendations relating to the application and end-use of all ITLS products are provided in good faith based on ITLS's knowledge and experience of the products. In applications, the differences in materials, and variances of substrates and actual site conditions can vary such that no warranty in respect of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be taken as inferred either from this information, or from any written recommendations, or from any other advice offered by ITLS. The proprietary rights of third parties must be observed. All orders are accepted subject to our sale terms and conditions. All users should always refer to the most recent and up to date issue of the Technical Data Sheet for the product concerned, which is available on request. It is recommended that products should always be properly stored, handled and applied under tested and recommended conditions. PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.