

ASAFLEX POWDER NSW Revision Number 2

Revision date 20-Feb-2022 Supersedes Date: 12-Oct-2016

Section 1: Identification: Product i	dentifier and chemical identity
Product identifier	
Product Name	ASAFLEX POWDER NSW
Product Code(s) 30840351 30840351	
Other means of identification	
Pure substance/mixture	Mixture
Recommended use of the chemica	l and restrictions on use
Recommended use	Adhesive
Uses advised against	No information available
Details of manufacturer or importe	<u>r</u>
Supplier Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria Australia Tel: 613 9279-9333 Fax: 613 9279-9342	
ABN: 79 003 893 838	
E-mail address	au-bostik-sds@bostik.com
Emergency telephone number Emergency telephone number	24-hr Emergency: 1800 033 111
Section 2: Hazard(s) identification	

GHS Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Specific target organ toxicity (single exposure)	Category 3 - (H335)

Label elements

Exclamation mark Corrosion

ASAFLEX POWDER NSW Revision Number 2

Revision date 20-Feb-2022 Supersedes Date: 12-Oct-2016



Signal word Danger

Hazard statements

H315 - Causes skin irritation H318 - Causes serious eye damage H335 - May cause respiratory irritation

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wear protective gloves/protective clothing/eye protection/face protection **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor IF ON SKIN: Wash with plenty of water and soap If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash it before reuse IF INHALED: Remove person to fresh air and keep comfortable for breathing Call a POISON CENTER or doctor if you feel unwell **Precautionary Statements - Storage** Store in a well-ventilated place **Precautionary Statements - Disposal** Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system.

Repeated exposure may cause skin dryness or cracking.

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

4

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	30 - 60
Calcium diformate	544-17-2	0 - <10
Calcium oxide	1305-78-8	0 - <10

ASAFLEX POWDER NSW Revision Number 2			Revision date 20-Feb-2022 Supersedes Date: 12-Oct-2016
	_	_	
Non-hazardous ingredients		Proprietary	Balance
Section 4: First aid measures			
Emergency telephone number	Poisons Information Cent Poisons Information Cent	er, Australia: 13 11 26 er, New Zealand: 0800 764 76	6
Description of first aid measures			
General advice	If medical advice is neede	ed, have product container or I	abel at hand.
Inhalation	Remove to fresh air. Get or concerned: Get medica		if symptoms occur. IF exposed
Eye contact		Immediately flush with plenty as and continue flushing for at	
Skin contact	Brush off loose particles f contaminated clothing and	rom skin. Remove material fro d wash before reuse.	m skin immediately. Take off
Ingestion	Rinse mouth. Never give a vomiting. Call a physician		nscious person. Do NOT induce
Self-protection of the first aider	Avoid contact with skin, e 8).	yes or clothing. Wear persona	I protective clothing (see section
Most important symptoms and effe	ects, both acute and delay	yed	
Symptoms	high concentration may ca water a strong alkaline so concrete may cause serio	ause irritation of respiratory sy	
Indication of any immediate medic	al attention and special t	reatment needed	
Note to physicians	Treat symptomatically.		
Section 5: Firefighting measures			
Suitable Extinguishing Media			
Suitable Extinguishing Media	Use extinguishing measur surrounding environment.	res that are appropriate to loca	al circumstances and the
Unsuitable extinguishing media	No information available.		
Specific hazards arising from the	chemical		
Specific hazards arising from the chemical	No information available.		
Hazardous combustion products	Carbon oxides. Silicon did	oxide.	
Special protective actions for fire-	fighters		
Special protective equipment and precautions for fire-fighters	Firefighters should wear s gear. Use personal protect		atus and full firefighting turnout

Section 6: Accidental release measures		
Personal precautions, protective equipment and emergency procedures		
Personal precautions	Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.	
Other information	Refer to protective measures listed in Sections 7 and 8.	
For emergency responders	Use personal protection recommended in Section 8.	
Environmental precautions		
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil.	
Methods and material for containr	nent and cleaning up	
Methods for containment	Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Prevent dust cloud.	
Methods for cleaning up	Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust.	
Precautions to prevent secondary	hazards	
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.	
Section 7: Handling and storage, including how the chemical may be safely used		
Precautions for safe handling		
Advice on safe handling	Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or clothing. Use personal protection equipment. Take off contaminated clothing and wash before reuse.	
General hygiene considerations	Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.	
Conditions for safe storage, including any incompatibilities		
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity.	
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.	
Section 8: Exposure controls and personal protection		

Control parameters

Exposure Limits

Chemical name	Australia
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1	10 mg/m³ TWA
Calcium oxide 1305-78-8	2 mg/m³ TWA

Appropriate engineering controls

Engineering controls	Showers, eyewash stations, and ventilation systems.	
Individual protection measures, such as personal protective equipment		
Eye/face protection	Tight sealing safety goggles.	
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing.	
Hand protection	Wear suitable gloves. Impervious gloves.	
Respiratory protection	Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.	
Environmental exposure controls	No information available.	

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Appearance Color Odor Odor threshold	Solid Powder Gray Slight No information available	
Property pH pH (as aqueous solution) Melting point / freezing point Initial boiling point and boiling range	Values No data available No data available Not applicable . °C Not applicable . °C	Remarks • Method Not applicable Insoluble in water
Flash point Evaporation rate Flammability Flammability Limit in Air	Not applicable . °C Not applicable . No data available	
Upper flammability or explosive limits Lower flammability or explosive limits Vapor pressure		
Relative vapor density Relative density Water solubility	No data available 1.6 Cement based products react and solidify in contact with water	
Solubility(ies) Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties	No data available No data available No data available No data available Not applicable . Not applicable . No information available No information available	
Other information Softening Point Solid content (%) Density VOC Content (%)	Not relevant No information available No information available < 1 g/L	SCAQMD Method 304-91

ASAFLEX POWDER NSW Revision Number 2

Section 10: Stability and reactivity		
<u>Reactivity</u>		
Reactivity	Product cures with moisture.	
Chemical stability		
Stability	Keep away from Incompatible materials. Stable under recommended storage conditions.	
Explosion data Sensitivity to mechanical impact	None.	
Sensitivity to static discharge	None.	
Possibility of hazardous reactions		
Possibility of hazardous reactions	None under normal processing.	
Conditions to avoid		
Conditions to avoid	Product cures with moisture.	
Incompatible materials		
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.	
Hazardous decomposition product	t <u>s</u>	
Hazardous decomposition products	None known based on information supplied.	
Section 11: Toxicological information		
Acute toxicity		
Information on likely routes of exp	osure	
Product Information		
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.	
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.	
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).	
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.	
Symptoms	Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.	
Numerical measures of toxicity -	Product Information	

Numerical measures of toxicity - Product Information

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Onennual name		Dermai LD30	

Cement, portland, chemicals (Chromium VI reduced)	-	>2000 Kg/mg (Lapin)	>5 g/m³ (Rattus)
Calcium diformate	=2650 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-
		OECD 402	
Calcium oxide	>2000 mg/kg (Rattus)	LD50 > 2500 mg/kg	> 6.04 mg/L (Rat) 4 h
		(Oryctolagus cuniculus)	

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Irritating to skin.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Risk of serious damage to eyes.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	May cause respiratory irritation.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Calcium diformate 544-17-2	RC50 (72h) > 1000 mg/l (Pseudokirchnerella subcapitata)	LC50: >=1000mg/L (96h, Brachydanio rerio)	-	EC50 (48h) > 1000 mg/l (Daphnia magna) EPA-660/3-75-009
Calcium oxide 1305-78-8	EC50 (Pseudokirchneriella subcapitata (green algae)): 106,02 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes	LC50 96 h = 50.6 mg/L (Oncorhynchus mykiss)	EC50 (Bacteria): 229,2 mg/l Exposure time: 3 h Test Type: static test Method: OECD Test Guideline 209 GLP: yes	EC50 (48h) = 49.1 mg/l(Daphnia magna) OECD 202

Persistence and degradability

Persistence and degradability

No information available.

Bioaccumulative potential					
Bioaccumulation	No information available.				
<u>Mobility</u>					
Mobility in soil	No information available.				
Mobility	No information available.				
Other adverse effects					
Other adverse effects	No information available.				
Section 13: Disposal considerations					
Disposal methods					
Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.				
Contaminated packaging	Do not reuse empty containers.				
Section 14: Transport information					
ADG	Not regulated				
ΙΑΤΑ	Not regulated				
IMDG	Not regulated				
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code					

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

<u>Australia</u>

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)Poison Schedule Number4

International Inventori	es
AIIC	Listed
NZIOC	Not Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed
PICCS	Not Listed

Legend:

ASAFLEX POWDER NSW Revision Number 2

AICS - Australian Inventory of Chemical Substances NZIOC - New Zealand Inventory of Chemicals

NZIOC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Revision date

20-Feb-2022

Revision Note

***Indicates updated data since last publication.

Section 12: Ecological information EC50 (effective concentration)

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: E	XPOSURE CONTROLS/PERSONAL PRO	TECTION					
TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)				
Ceiling	Maximum limit value	*	Skin designation				
С	Carcinogen		-				
Section 11: TOXICOLOGICAL INFORMATION							
LD50 (lethal	dose)						

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet