



BOSTIK EPOXY RAPID

RAPID CURING 2-COMPONENT ADHESIVE

30th July 2020

YOUR SMART ADVANTAGES

- Incredibly strong
- Quick bonding Epoxy
- Heat, water, chemical and oil resistant
- Can be sanded and painted
- Tray and spatula included

DESCRIPTION

Bostik Epoxy Rapid is a two-component Epoxy glue in a convenient syringe. Accelerated bonding with a five-minute hold, it is ultra-resistant, withstanding extreme temperatures from -30°C to +70°C. Withstands rough handling and fills uneven surfaces. Moisture resistance makes it suitable in a wide range of applications.

USES

Suitable for indoor and outdoor uses.

For use on metal, wood, masonry, ceramics, glass, leather, rubber, chipboard, stone, plastic, concrete, cardboard, fabric and most plastics.

PRODUCT CHARACTERISTICS

Form	Liquid
Colour	Colourless to yellow
Packaging Form	Two-component syringe
Odour	Ammonia
Product codes	
25ml Blister	30617844

TYPICAL PERFORMANCE DATA (Approx.)

Final strength	130 Kg/cm ²
Fixture time	5 minutes
Flash Point	150°C
Bond Time	2 hours
Maximum Performance	24 hours
Heat Resistant	High

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Epoxy Rapid, refer to the relevant Safety Data Sheet, available at www.bostik.com.au

PREPARATION

1. Make sure all surfaces to be bonded are clean, dry, and free from dust and grease.

APPLICATION

2. Remove the resealable cap from the plunger and snap the tabs off both nozzles.
3. Push down the plunger to dispense equal amounts of the two adhesive components onto the tray provided.
4. Mix the components thoroughly for 45 seconds with spatula provided. Use the adhesive within three minutes.
5. Apply the adhesive to both surfaces with the spatula and press them together. Keep the joint supported until set. Allow at least 10 minutes before handling.

CLEANING

6. Attach the resealable cap to the nozzles. Carefully remove any excess adhesive with a sharp knife before it sets.

PRECAUTIONS IN USE

1. Use in a well-ventilated area.
2. To avoid adhesive whitening, do not apply in hot temperatures or high humidity and ensure that vapours can escape.
3. Not recommended on paper, plastics with an oily/waxy appearance e.g. polyethylene, polypropylene or Teflon. Will not permanently bond glass or materials containing a high alkaline content.

For any application not covered please contact Technical Services on 1800 267 845 or visit www.bostik.com.au for advice.

BOSTIK EPOXY RAPID

STORAGE AND SHELF LIFE

Store for up to 24 months from date of manufacture, when stored in the original, unopened packaging under dry conditions, and within the temperature range of +5°C to +25°C.

Keep container tightly closed and store in a dry, cool and well-ventilated place. Store locked up.

HEALTH & SAFETY

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

If poisoning occurs, contact Poisons Information Centre
Phone 131126

FIRST AID

Swallowed: Do NOT induce vomiting, give a glass of water and contact a doctor immediately.

Skin: If irritation or allergic reaction occurs, discontinue use and seek medical advice.

Eyes: Hold eyes open and flood with water for at least 15 minutes, removing any contact lenses if easy to do so. Seek medical attention.

Always read the Technical Data Sheet and Safety Data Sheet (SDS) before handling or use. Full product safety information required for safe use is not included in this data sheet. SDS available by request or at www.bostik.com.au

Recommendations and suggestions are for guidance only, since conditions of use are completely out of our control.

For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.

BOSTIK HOTLINE

Smart help 1800 267 845



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com.au