#### MATERIAL SAFETY DATA SHEET

## SLIDE PRODUCTS, INC. 430 S. WHEELING ROAD WHEELING, IL 60090

## PRODUCT NAME: SLIDE P.D.Q.-PURGING COMPOUND

EMERGENCY TELEPHONE: 800-530-5053 INFORMATION TELEPHONE: 847-541-7220

FAX NUMBER: 847-541-7986 PREPARED BY: JIM ARMSTRONG REVISION DATE: SEPT. 1, 2012 PRODUCT NUMBER: 43432/43401 D.U.N.S. NUMBER: 00-299-4168

## SECTION I. IDENTIFICATION

CHEMICAL NAME: N/A

CHEMICAL FAMILY: WATER BASED EMULSION

FORMULA: 43432/01 SYNONYMS: NONE

DOT HAZARD CLASSIFICATION: NOT HAZARDOUS

DOT SHIPPING NAME: NOT ASSIGNED

CHEMICAL ABSTRACT REGISTRY NUMBER: N/A - MIXTURE

IDENTIFICATION NUMBER: NOT ASSIGNED

H.M.I.S. RATING: 1,0,0,A

# SECTION II. PHYSICAL DATA

BOILING POINT: 212' F. FREEZING POINT: 32' F.

SPECIFIC GRAVITY (H20 =1): 1.13 WEIGHT PER GALLON @ 60 F.: 9.43 VAPOR PRESSURE @ 70 F. (MM HG): 17

VAPOR DENSITY (AIR = 1): .6

SOLUBILITY IN WATER, % BY WT.: COMPLETELY MISCIBLE

PERCENT VOLATILE BY VOLUME: 72% EVAPORATION RATE (WATER =1): 1

APPEARANCE AND ODOR: PALE STRAW, CREAMY EMULSION-MILD ODOR

### SECTION III. HAZARDOUS INGREDIENTS

| MATERIAL:  | APPROX. WEIGHT%: | CAS NUMBER: | TLV(UNITS) |
|------------|------------------|-------------|------------|
| OLEIC ACID | 5-10             | 112-80-1    | N/A        |
| MORPHOLINE | 1-10             | 110-91-8    | 20 PPM     |
| SILICA     | 18-28            | 14808-60-7  | N/A        |
| WATER      | 60-70            | 7732-18-5   | N/A        |

<sup>\*\*</sup> CONTAINS NO OZONE DEPLETING CHEMICALS \*\*

## SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: N/A UEL: N/A (VOLUME %)

FLASH POINT: NO FLASH

SPECIAL FIRE FIGHTING PROCEDURES: NONE UNUSUAL FIRE & EXPLOSION HAZARDS: NONE

## SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): HAZARDOUS COMBUSTION BY-PRODUCTS:

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR CONDITIONS TO AVOID: KEEP FROM FREEZING

### SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: N/A

### • EFFECTS OF OVER EXPOSURE \*

INGESTION(SWALLOWING): NAUSEA

INHALATION: N/A

SKIN EFFECT: NO EFFECT

EYE CONTACT: TEMPORARY IRRITATION

### • EMERGENCY AND FIRST AID PROCEDURES \*

INGESTION: INDUCE VOMITING BY GIVING WARM WATER, CALL PHYSICIAN

SKIN: WASH WITH SOAP AND WATER

INHALATION: N/A

EYES: RINSE WITH COOL CLEAN WATER UNTIL IRRITATION SUBSIDES

## SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: WIPE UP SPILL WASTE DISPOSAL METHOD: STANDARD FOR INDUSTRIAL OPERATIONS

## SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED

VENTILATION: ADEQUATE VENTILATION NEEDED

PROTECTIVE GLOVES: NOT REQUIRED BUT RECOMMENDED EYE PROTECTION: NOT REQUIRED BUT RECOMMENDED

OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

## SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS – DO NOT ALLOW TO FREEZE.

OTHER PRECAUTIONS: SEE P.D.Q. DATA SHEET FOR PROPER USE INSTRUCTIONS.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THSES RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

http://www.slideproducts.com/purging.htm