Model	STC-1000Pro	STC-1000WiFi	STC-1000Pro TH	STC-1000WiFi TH
Prodcut Image				
Working Voltage	110V(US Plug); 220V(UK, EU plug)			
Relay Contact Output Capacity	10A (resistive) / 110V (US Plug); 220V(UK, EU plug)			
Temperature Control Range	-40°C~110°C/-40°F~230°F		-5°C~70°C/23°F~158°F	
Humidity Control Range			5~99%RH	
Temperature Accuracy	±1°C/±2°F		±0.5°C/±1°F	
Humidity Accuracy			±5%RH	
Sensor Type	NTC Temperature Sensor		NTC Temperature&Humidity Sensor	
Audible Alarm	1	✓	✓	✓
Temperature Calibration	✓	1	√	1
Humidity Calibration			✓	1
Temperature Unit	°C/°F			
Start Delay	✓	1	√	√
Wi-Fi Function ¹		1		√
Wi-Fi Type		2.4G only		2.4G only
Backlight	5Mins	0-10Hrs	0-999Mins	0-999Mins
Working Mode	Cooling & Heating		Work1 for Temperature; Work2 for Humidity	
Version Available	US/UK/EU Plug			
Applications	Elitech STC-1000Pro series temperature controllers are mainly used in grow rooms, aquariums, pet breeding incubations, seedling mats, greenhouses, and other scenarios.			
1. Wi-Fi Function allows users to se	et parameters, turn on/off the	e device, and view data, grap	h, alarm history remotely o	n mobile app.