



Professional precise glue dispenser DIS-127 adopts the latest digital control system, assure timing output consistently. Friendly user, simpler operation, easier coating, lineation and drop, highlight high-quality products, improve production efficiency. This dispenser can be used on different occasions for long time. It's widely used on electronics, aviation, optics, chemistry, automobile, medical treatment, petroleum, packaging, jewellery and machinery industry.



DESCRIPTION

- Manual or timer operation modes
- Digital display
- Free to set 16 different modes
- Foot pedal controlled (finger switch option)
- Suck-back feature ensure no dripping
- Designed for wide range of application as EFD I&J, Fisnar
- Timer mode dispensing time 0.01-99.99sec
- Timer mode cycle intervals 0.1-9.9sec
- Manual mode: materials could be dispensed continuously until the operator releases the foot pedal
- Manual timing dispensing: can dispense continuously and with repeatability while a determined timing is set-up simply by pressing the pedal
- This unit needs to be connected to air compressor (1.5HP or above= 1.1kW or above)

TECHNICAL DETAILS

Net weight	2.2 Kg
Dimensions	23.5 x 15.6x 5.8cm
Minimum quantity which can be dispensed	Circa 0,001 to 0,0001ml
Timer mode dispensing time	0.01-99.99sec
Timer mode cycle interval	0.1-9.9sec
Input voltage	220V±10% 50 Hz.
Internal voltage	24V DC
Air input	10-100psi (0.7 to 6.8bars)
Air output	1-80psi (0.07 to 5.5bars)

ACCESSORIES DELIVERED TOGETHER

- Foot switch pedal (possible option on a finger switch)
- Electrical plug (European, UK or Swiss type...)
- Air inlet
- Air outlet with its connection for 3cc, 10cc, 30cc or 55cc barrel
- Cartridge holder
- 1 cartridge and 2 needles with the size of your choice
- Instructions manual