

THE ALL NEW

NOTHING STAYS THE SAME.



# 

### A MILESTONE FOR PURE WATER CLEANING: THE ALL NEW nLITE WATERFED POLE SYSTEM

It's high time to take cleaning with pure water to a new dimension and era.

It's time to invent a whole new form of telescopic waterfed pole technology.

It's time for a game changer:

### THE ALL NEW nLITE

### **NOTHING STAYS THE SAME!**

**UNGER** is now setting aside the achievements of the past and is once again proving its unconditional will, innovative pioneering spirit, and courageous foresight.

Discover the best and most advanced telescopic waterfed pole system today:

LIGHTER, MORE PRECISE, FASTER.



### **SMARTLOCK CLAMPS**

- · Easy and quick to close with just one finger
- Robust 2C material
- Clamp mechanism that protects the carbon material and ensures a long service life for the pole
- Extension stop prevents pulling out pole elements too far



Internal routing of the new, highly flexible DuroFlex hose in the telescopic pole for trouble-free work on windows and facades.

Complete flexibility: external routing possible thanks to optional nLite clips.







## TOP PERFORMANCE THROUGH PROGRESS

Innovation, high quality, and customer-oriented development have always been **UNGER**'s guiding principles. This applies once again to the new generation of the **nLite** telescopic pole system:

- German engineering in a timelessly stylish design
- Intelligent solution for faster, more flexible system setup
- Pioneering technologies for more effective cleaning results
- High Quality Made in Germany



### **HIGH-END CARBON MATERIALS**

Ultra-lightweight. Extremely durable. Two choices of carbon:

- CARBON COMPOSITE: High quality mix of carbon and glass fibres
- CARBON 24K: Premium carbon fibres in a unique weave of 24,000 fibres per bundle





1×

### MORE STABLE, HIGHER, **MORE PRECISE, WOW!**

UNGER has developed its new nLite telescopic poles to take your performance to new heights. Maximising refined details and precision while minimising time and effort spent getting organised for your work.

- No twisting: trouble-free work and less wear and tear
- Optimal stability-to-weight ratio
- · Greater pole rigidity
- . More precise control of the cleaning movement

### **POWER BRUSH AND ANGLE ADAPTER**

Innovative modular system that makes a difference because it offers almost limitless application options:

- · 2 brush widths combined with further equipment options
- Gooseneck adapter system = maximum flexibility even in hard-to-reach places

### **TELESCOPIC MAIN POLE**

6-sections main telescopic pole:

- Carbon 24K can be extended with up to 2 extension poles.
- Length 8.6 m (collapsed 1,7 m) means you can reach the second floor
- Optimal diameter for perfect ergonomic

### **EXTENSION ADAPTER**

Connects the first telescopic extension pole to the telescopic main pole with internal hose routing.



### **TELESCOPIC EXTENSION** POLE

2-sections telescopic extension pole:

- Length 3.2 m (collapsed 1,8 m) = one floor
- With Carbon 24K, up to 2 extension poles can be used
- Working heights up to 16,20 m
- · Constant and optimal diameter for every length





**UP TO** 

2×




### UNPRECEDENTED DIMENSIONS IN WINDOW CLEANING

The pole lengths offered by the all new **nLite** system have been created and optimised for your everyday work.

From now on, you can easily think of how many floors' you can clean. The telescopic main pole now measures  $8.6\,\text{m}$ , so it extends to the 2nd floor. Each extension pole offers exactly the additional length to take you up another storey  $(3.05\,\text{m})$ .

For use in less high buildings or with a boom lift, we have the right solution for you with telescopic poles ranging from 1.6 m to 6 m in length.


**UNGER** guarantees the best possible premium quality in each of the 2 material classes used and thus the perfect solution for every working height.



Carbon COMPOSITE

**RESILIENCE: 100 GPa** 

Recommended for working heights of up to 10 m



### Carbon 24k

**RESILIENCE: 210 GPa** 

Recommended for working heights of up to 16 m



### **RINSE BAR**

This special flushing nozzle bar is attached above the brush and delivers the right amount of pure water exactly where it is needed for powerful rinsing of the cleaned surface - surface - more effective than ever before! Ideal in connection with the swivel function

 Water jets from the nozzle block built into the middle of the brush ensure powerful dirt removal

### **POWER BRISTLE TECHNOLOGY**

- Inner bristles with extremely high cleaning performance, comparable to natural hair bristles
- B Longer outer bristles for easy gliding: no more annoying jumping of the brush

### **SOFT TOUCH BUMPER**

The edge protection made of soft plastic:

- Safe protection against scratches and other damage to window frames
- Significant noise reduction when coming into contact with parts of the building


## ON TOP: SWIVEL FUNCTION AND POWER BRISTLE TECHNOLOGY

Outstanding down to the last detail: a fully optimized brush concept prepares you for almost any challenge.

- Clever water distribution system
- Innovative bristle technology
- Precision cleaning down to the last corner
- Ultimate cleaning performance for perfect results











• The brush socked, which can be swivelled freely through 180°, enables the surface to be cleaned

You've never cleaned faster and more precisely down to the last corner: the swivel function is a completely new way of cleaning with pure water up to the first floor (6 m). Open the SwivelLock and



**SWIVEL LOCK** 

experience the advantages:





### MODULAR ANGLE ADAPTER SYSTEM: CLEAN HARD-TO-REACH PLACES

Another clever feature of the new **nLite** pole system is the modular angle system, in which you can combine four individual elements in any number of variants in order to easily reach places that are difficult to access. Whether conservatories or overhanging façade elements, this system gives you the perfect angle for every application.

Simply adapt the modular angle adapter individually to your application. The angle is freely adjustable and quickly fixed with the clamps.

- A Pole adapter
- B Brush adapter
- C Angle element short
- Angle element long

### **FAST LOCK**

With a single click: simple, fast, and stable connection for every work situation:

- Change brushes in seconds
- Adjust brush angle in 45° stages
- No twisting when cleaning!




# HYDRO POWER: OUR INNOVATIVE AND EFFICIENT PURE WATER FILTERS

If you want to clean with the most advanced telescopic pole system, the right pure water filter is indispensable. Depending on your individual requirements, choose between DI or RO in different performance classes. Here you will find the solution that fits your requirements:

ungerglobal.com/en/applications/pure-water-cleaning-system







### **PRODUCT OVERVIEW**

25 m

### nLITE® Telescopic poles

	Part No.	Info	nded	Collapsed	Sections	Pack
	CC16T	Telescopic pole	1,6 m	0,9 m	2	1
CARBON	CC32T	Telescopic pole	3,2 m	1,7 m	2	1
	CC60T	Telescopic pole	6,0 m	1,7 m	4	1
	CC85T	Telescopic pole	8,6 m	1,7 m	6	1
	CC85H	Telescopic pole CC85T, Angle adapter NGS15, Power brush NFF28, Hose DLS25				
CARBON 24K	CF60T	Telescopic pole	6,0 m	1,7 m	4	1
		• •	· · · · · · · · · · · · · · · · · · ·			1
	CF86G	Telescopic main pole, extendable	8,6 m	1,7 m	6	1
	CF33G	Telescopic extension pole	3,2 m	1,8 m	2	1
	CF12H	Telescopic main pole CF86G, Extension adapter NLHCC, Telescopic expansion pole CF33G, Angle adapter NGS30, Power brush NFF28, Hose DLS25				

LITE® Power Brushes, Angle Adapters and Accessories									
	Part No.	Info	Width	Bristles	Pack				
	NFF28	Power brush, simple	28 cm	spliced	1				
	NFF41	Power brush, simple	41 cm	spliced	1				
	NUF28	Power brush, simple	28 cm	unspliced	1				
	NUF41	Power brush, simple	41 cm	unspliced	1				
v	NFK28	Power brush complete (bumper, swivel function, rinse bar)	28 cm	spliced	1				
H.	NFK41	Power brush complete (bumper, swivel function, rinse bar)	41 cm	spliced	1				
3RU	NUK28	Power brush complete (bumper, swivel function, rinse bar)	28 cm	unspliced	1				
POWER BRUSHES	NUK41	Power brush complete (bumper, swivel function, rinse bar)	41 cm	unspliced	1				
WO	NFA28	Power brush for nLite® Connect poles (w/ bumper, rinse bar), angle adapter (FTGOS)	28 cm	spliced	1				
Δ.	NFA41	Power brush for nLite® Connect poles (w/ bumper, rinse bar), angle adapter (FTGOS)	41 cm	spliced	1				
	NUA28	Power brush for nLite® Connect poles (w/ bumper, rinse bar), angle adapter (FTGOS)	28 cm	unspliced	1				
	NUA41	Power brush for nLite® Connect poles (w/ bumper, rinse bar), angle adapter (FTGOS)	41cm	unspliced	1				
	NFS28	Soft brush for gentle surface cleaning (w/ bumper, swivel function, rinse bar)	28 cm	synthetic, 2,5cm	1				
BRUSHES	NFS41	Soft brush for gentle surface cleaning (w/ bumper, swivel function, rinse bar)	41 cm	synthetic, 2,5cm	1				
RUS	NUH28	Hybrid brush w/extremely powerful cleaning performance (w/ bumper, swivel function, rinse bar)	28 cm	Natural bristles+Power	1				
<b>"</b>	NUH41	Hybrid brush w/extremely powerful cleaning performance (w/ bumper, swivel function, rinse bar)	41 cm	Natural bristles+Power	1				
	Part No.	Info	Length		Pack				
<u>د</u>	NGS15	Angle adapter kit S	15 cm		1				
ANGLE ADAPTER	NGS30	Angle adapter kit M	42 cm		1				
AAD	NGS45	Angle adapter kit L	82 cm		1				
	Part No.	Info	Length	Diematre	Pack				
	NLHCC	Extension adapter	40 cm		1				
	NLTHR	Euro-thread adaüter for brushes	-		1				
ES	NLCLA	Adapter for traditional window cleaning tools	-		1				
SOR	NLWVI	Water flow regulator for DLS25	-	Ø 5/8 mm	1				
ACCESSORIES	22818	Water flow regulator for DLH25	-	Ø 7/10 mm	1				
	NLHKP	Clips for outer hose routing	-		6				
	DLS25	DuroFlex hose, Ø 8mm outside, 5mm inside	25 m		1				

**UNGER Germany GmbH** Piepersberg 44 D-42653 Solingen Germany Tel.: (49) 212 2207 260 Fax: (49) 212 2207 222

DLH25

ungereurope@ungerglobal.com www.ungerglobal.com

The general terms of delivery and payment of Unger Germany GmbH apply. Valid from 01.01.2022. With any orders placed by our commercial trade customers and with our deliveries. All data is without guarantee. Subject to alterations.

DuroFlex high performance hose,  $\emptyset$  10mm outside, 7mm inside









