SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

CREATE FREE Clear (THIS) Part B

of the mixture

Registration number

Synonyms None.

Issue date 22-January-2018

Version number 01 **Revision date** Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Dry erase paint. Uses advised against None known. 1.3. Details of the supplier of the safety data sheet

IdeaPaint LTD Manufacturer/Supplier

5 New Street Square London, EC4A 3TW +44 207 837 9922 dclark@ideapaint.com

e-mail **Dugald Clark Contact person**

+44 8 08 189 0979 **Emergency**

Access Code: 333641

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Telephone number

H302 - Harmful if swallowed. Acute toxicity, oral Category 4 Skin corrosion/irritation Category 1B H314 - Causes severe skin burns

and eye damage.

Serious eye damage/eye irritation Category 1 H318 - Causes serious eye

damage.

Skin sensitisation Category 1 H317 - May cause an allergic skin

reaction.

Hazard summary Causes severe skin burns and eye damage. Harmful if swallowed. May cause an allergic skin

reaction. Occupational exposure to the substance or mixture may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 3-Aminopropyltriethoxysilane

Hazard pictograms



Signal word Danger

Hazard statements

Harmful if swallowed. H302

Causes severe skin burns and eye damage. H314

May cause an allergic skin reaction. H317

Causes serious eye damage. H318

CREATE FREE Clear SDS EU (THIS) Part B 942281 Revision date: -Issue date: 22-January-2018

Precautionary statements

Prevention

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P310 Immediately call a POISON CENTRE/doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage Not assigned.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
3-Aminopropyltriethoxysilan	e 100	919-30-2 213-048-4	-	612-108-00-0	
Classification: A	cute Tox 4:H302 Sk		n Sens. 1;H317, Eye Dam. 1	1·H318	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated

clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control centre immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Provide eyewash station.

Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison

control centre immediately.

Ingestion Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and

delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Will burn if involved in a fire.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

Unsuit media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

CREATE FREE Clear
(THIS) Part B 942281 Revision date: - Issue date: 22-January-2018 2 / 10

Move containers from fire area if you can do so without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during

clean-up.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe mist or vapour. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. Persons susceptible to allergic reactions should not handle this product. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials

Value

(see section 10 of the SDS).

Type

Dry erase paint. 7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

Revision date: -

8.1. Control parameters

Occupational exposure limits

Austria. MAK List Additional components

Additional components	туре	value
Ethanol (CAS 64-17-5)	Ceiling	3800 mg/m3
		2000 ppm
	MAK	1900 mg/m3
		1000 ppm
Belgium. Exposure Limit Values.		
Additional components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1907 mg/m3
		1000 ppm
Bulgaria. OELs. Regulation No 13	on protection of workers agai	inst risks of exposure to chemical agents at work
Additional components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3
Croatia. Dangerous Substance E	xposure Limit Values in the Wo	orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09
Additional components	Туре	Value
Ethanol (CAS 64-17-5)	MAC	1900 mg/m3
,		1000 ppm
Czech Republic. OELs. Governm	ent Decree 361	
Additional components	Туре	Value
Ethanol (CAS 64-17-5)	Ceiling	3000 mg/m3
	TWA	1000 mg/m3
Denmark. Exposure Limit Values		
Additional components	Туре	Value
Ethanol (CAS 64-17-5)	TLV	1900 mg/m3

CREATE FREE Clear SDS EU

Type

Value

1000 ppm

Additional components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
Ethanor (CAS 04-17-5)	SILL	1000 ppm
	TWA	1000 ppm 1000 mg/m3
	IVVA	G
		500 ppm
inland. Workplace Exposure Limit	ts	
Components	Туре	Value
3-Aminopropyltriethoxysilan	STEL	55 mg/m3
e (CAS 919-30-2)	SIEL	55 mg/ms
0 (0/10 010 00 2)		6 ppm
	TWA	28 mg/m3
	1 447 (3 ppm
Additional components	Type	Value
Additional components	Туре	value
Ethanol (CAS 64-17-5)	STEL	2500 mg/m3
		1300 ppm
	TWA	1900 mg/m3
		1000 ppm
France Threshold Limit Values (VI	ED) for Occupational Expos	ure to Chemicals in France, INRS ED 984
Additional components	Type	Value
·		0500
Ethanol (CAS 64-17-5)	VLE	9500 mg/m3
		5000 ppm
	VME	1900 mg/m3
		1000 ppm
· · ·	·	nvestigation of Health Hazards of Chemical Compou Value
Additional components	Type TWA	
th the Work Area (DFG) Additional components Ethanol (CAS 64-17-5)	Туре	Value
Additional components Ethanol (CAS 64-17-5)	Type TWA	Value 960 mg/m3 500 ppm
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values i	Type TWA	Value 960 mg/m3 500 ppm
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values i Additional components	Type TWA in the Ambient Air at the World Type	Value 960 mg/m3 500 ppm rkplace Value
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components	Type TWA in the Ambient Air at the Wor	Value 960 mg/m3 500 ppm rkplace Value 960 mg/m3
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5)	Type TWA in the Ambient Air at the Wor Type AGW	Value 960 mg/m3 500 ppm rkplace Value
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999,	Type TWA in the Ambient Air at the Wor Type AGW	Value 960 mg/m3 500 ppm *kplace Value 960 mg/m3 500 ppm
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999,	Type TWA in the Ambient Air at the Wor Type AGW	Value 960 mg/m3 500 ppm rkplace Value 960 mg/m3
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components	Type TWA in the Ambient Air at the Wor Type AGW as amended) Type	Value 960 mg/m3 500 ppm rkplace Value 960 mg/m3 500 ppm Value
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components	Type TWA in the Ambient Air at the Wor Type AGW as amended)	Value 960 mg/m3 500 ppm *kplace Value 960 mg/m3 500 ppm Value 1900 mg/m3
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5)	Type TWA in the Ambient Air at the Word Type AGW as amended) Type TWA	Value 960 mg/m3 500 ppm Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on CI	Type TWA in the Ambient Air at the Wor Type AGW as amended) Type TWA hemical Safety of Workplace	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on CI	Type TWA in the Ambient Air at the Word Type AGW as amended) Type TWA	Value 960 mg/m3 500 ppm Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components	Type TWA in the Ambient Air at the Wor Type AGW as amended) Type TWA hemical Safety of Workplace Type	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm s Value
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values i	Type TWA in the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm s Value 7600 mg/m3
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5)	Type TWA in the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm S Value 7600 mg/m3 1900 mg/m3
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) Celand. OELs. Regulation 154/1998	Type TWA In the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure in	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm s Value 7600 mg/m3 1900 mg/m3 1900 mg/m3 imits
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) Celand. OELs. Regulation 154/1998	Type TWA in the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm S Value 7600 mg/m3 1900 mg/m3
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) Celand. OELs. Regulation 154/1998 Additional components	Type TWA In the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure in	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm s Value 7600 mg/m3 1900 mg/m3 1900 mg/m3 imits
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) Celand. OELs. Regulation 154/1998 Additional components	Type TWA in the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure I	Value 960 mg/m3 500 ppm rkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm s Value 7600 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) celand. OELs. Regulation 154/1998 Additional components Ethanol (CAS 64-17-5)	Type TWA in the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure I Type TWA	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm s Value 7600 mg/m3 1900 mg/m3 1900 mg/m3 imits Value
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) celand. OELs. Regulation 154/1998 Additional components Ethanol (CAS 64-17-5) reland. Occupational Exposure Lire	Type TWA in the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure I Type TWA TWA	Value 960 mg/m3 500 ppm Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm S Value 7600 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) celand. OELs. Regulation 154/1998 Additional components Ethanol (CAS 64-17-5) reland. Occupational Exposure Lire	Type TWA in the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure I Type TWA	Value 960 mg/m3 500 ppm rkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm s Value 7600 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) celand. OELs. Regulation 154/1998 Additional components Ethanol (CAS 64-17-5) reland. Occupational Exposure Line Additional components	Type TWA in the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure I Type TWA TWA	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1900 mg/m3 1900 mg/m3 imits Value 1900 mg/m3 1000 ppm Value
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) celand. OELs. Regulation 154/1998 Additional components Ethanol (CAS 64-17-5) reland. Occupational Exposure Line Additional components Ethanol (CAS 64-17-5)	Type TWA In the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure I Type TWA TWA TWA TWA TWA	Value 960 mg/m3 500 ppm Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm S Value 7600 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) Celand. OELs. Regulation 154/1998 Additional components Ethanol (CAS 64-17-5) reland. Occupational Exposure Line Additional components Ethanol (CAS 64-17-5) taly. OELs	Type TWA in the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure I Type TWA mits Type STEL STEL TWA STEL TWA Type TWA	Value 960 mg/m3 500 ppm Value 960 mg/m3 500 ppm Value 1900 mg/m3 1000 ppm S Value 7600 mg/m3 1900 mg/m3 1900 mg/m3 1900 mg/m3 1000 ppm Value 1900 mg/m3 1000 ppm Value 1900 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit Values in Additional components Ethanol (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, Additional components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree on Cladditional components Ethanol (CAS 64-17-5) celand. OELs. Regulation 154/1998 Additional components Ethanol (CAS 64-17-5) reland. Occupational Exposure Line Additional components	Type TWA In the Ambient Air at the Work Type AGW as amended) Type TWA hemical Safety of Workplace Type STEL TWA on occupational exposure I Type TWA TWA TWA TWA TWA	Value 960 mg/m3 500 ppm Pkplace Value 960 mg/m3 500 ppm Value 1900 mg/m3 1900 mg/m3 1900 mg/m3 imits Value 1900 mg/m3 1000 ppm Value

CREATE FREE Clear SDS EU (THIS) Part B 942281 Revision date: - Issue date: 22-January-2018

Additional components	mit values of chemical sub Type	Value
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3
Lithuania. OELs. Limit Values for Cher	nical Substances, General	Requirements (Hygiene Norm HN 23:2007)
Additional components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
,		1000 ppm
	TWA	1000 mg/m3
		500 ppm
Netherlands. OELs (binding)		
Additional components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
	TWA	260 mg/m3
Norway. Administrative Norms for Con	taminants in the Workplace	·
Additional components	Туре	Value
Ethanol (CAS 64-17-5)	TLV	950 mg/m3
	ILV	500 ppm
Deland MACe Description researding to	avimum narmiaaibla aana	• •
environment, Annex 1	aximum permissible conce	entrations and intensities of harmful factors in the wor
Additional components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
,		· ·
Portugal. VLEs. Norm on occupational Additional components	exposure to chemical ager Type	its (NP 1796) Value
Ethanol (CAS 64-17-5)	TWA	1000 ppm
,		• •
Romania. OELs. Protection of workers Additional components	Type	Value
Ethanol (CAS 64-17-5)	STEL	9500 mg/m3
,		•
		3000 ppiii
	TWA	5000 ppm 1900 mg/m3
	TWA	·
Slovakia. OELs. Decree of the governm		1900 mg/m3 1000 ppm
——————————————————————————————————————		1900 mg/m3 1000 ppm
Slovakia. OELs. Decree of the governm agents Additional components		1900 mg/m3 1000 ppm
agents Additional components	ent of the Slovak Republic	1900 mg/m3 1000 ppm concerning protection of health in work with chemica Value
agents Additional components	ent of the Slovak Republic	1900 mg/m3 1000 ppm concerning protection of health in work with chemica
Additional components Ethanol (CAS 64-17-5)	Type	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200	Type	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm
agents Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components	Type TWA Or concerning protection o	1900 mg/m3 1000 ppm concerning protection of health in work with chemica Value 960 mg/m3 500 ppm f health in work with chemical agents Value
agents	Type TWA Toncerning protection o	1900 mg/m3 1000 ppm concerning protection of health in work with chemica Value 960 mg/m3 500 ppm f health in work with chemical agents
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5)	Type TWA Type Trype Trype Trype Type STEL	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning	Type TWA Type TWA Type TSTEL Type STEL	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovenia)	Type TWA Type TWA Type TSTEL Type STEL	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovadditional components	Type TWA Type TWA Type STEL Type Type Type Type Type Type Type Typ	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while working
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovadditional components	Type TWA Of concerning protection of Type STEL og protection of workers agreenia)	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while working Value 1900 mg/m3
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovadditional components Ethanol (CAS 64-17-5)	Type TWA Type TWA Type STEL Type Type Type Type Type Type Type Typ	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while working
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovadditional components Ethanol (CAS 64-17-5) Spain. Occupational Exposure Limits	Type TWA 7 concerning protection of Type STEL 1 g protection of workers agreeman Type Twa Type TWA	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while working Value 1900 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovalditional components Ethanol (CAS 64-17-5) Spain. Occupational Exposure Limits Additional components	Type TWA 7 concerning protection of Type STEL 1 g protection of workers agrenia) Type TWA Type TWA	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while workin Value 1900 mg/m3 1000 ppm Value
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concernin (Official Gazette of the Republic of Slov Additional components Ethanol (CAS 64-17-5) Spain. Occupational Exposure Limits Additional components	Type TWA 7 concerning protection of Type STEL 1 g protection of workers agreeman Type Twa Type TWA	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm rainst risks due to exposure to chemicals while working Value 1900 mg/m3 1000 ppm Value 1910 mg/m3
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovadditional components Ethanol (CAS 64-17-5) Spain. Occupational Exposure Limits Additional components Ethanol (CAS 64-17-5)	Type TWA 7 concerning protection of Type STEL 7 protection of workers agrenia) Type TWA Type TWA Type STEL	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while working Value 1900 mg/m3 1000 ppm Value 1910 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovadditional components Ethanol (CAS 64-17-5) Spain. Occupational Exposure Limits Additional components Ethanol (CAS 64-17-5) Sweden. OELs. Work Environment Aut	Type TWA 77 concerning protection of Type STEL 18 protection of workers agrenia) Type TWA Type TWA Type STEL Type TWA Type STEL	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while workin Value 1900 mg/m3 1000 ppm Value 1910 mg/m3 1000 ppm Exposure Limit Values (AFS 2015:7)
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovadditional components Ethanol (CAS 64-17-5) Spain. Occupational Exposure Limits Additional components Ethanol (CAS 64-17-5) Sweden. OELs. Work Environment Aut	Type TWA 7 concerning protection of Type STEL 7 protection of workers agrenia) Type TWA Type TWA Type STEL	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while working Value 1900 mg/m3 1000 ppm Value 1910 mg/m3 1000 ppm
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovalditional components Ethanol (CAS 64-17-5) Spain. Occupational Exposure Limits Additional components	Type TWA 77 concerning protection of Type STEL 18 protection of workers agrenia) Type TWA Type TWA Type STEL Type TWA Type STEL	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while workin Value 1900 mg/m3 1000 ppm Value 1910 mg/m3 1000 ppm Exposure Limit Values (AFS 2015:7)
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovadditional components Ethanol (CAS 64-17-5) Spain. Occupational Exposure Limits Additional components Ethanol (CAS 64-17-5) Sweden. OELs. Work Environment Autoritional components	Type TWA 7 concerning protection of Type STEL 19 protection of workers agrenia) Type TWA Type TWA Type STEL hority (AV), Occupational E	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while working Value 1900 mg/m3 1000 ppm Value 1910 mg/m3 1000 ppm Exposure Limit Values (AFS 2015:7) Value
Additional components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 300/200 Additional components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations concerning (Official Gazette of the Republic of Slovadditional components Ethanol (CAS 64-17-5) Spain. Occupational Exposure Limits Additional components Ethanol (CAS 64-17-5) Sweden. OELs. Work Environment Authadditional components	Type TWA 7 concerning protection of Type STEL 19 protection of workers agrenia) Type TWA Type TWA Type STEL hority (AV), Occupational E	1900 mg/m3 1000 ppm concerning protection of health in work with chemical Value 960 mg/m3 500 ppm f health in work with chemical agents Value 1920 mg/m3 1000 ppm ainst risks due to exposure to chemicals while working Value 1900 mg/m3 1000 ppm Value 1910 mg/m3 1000 ppm Exposure Limit Values (AFS 2015:7) Value 1900 mg/m3

CREATE FREE Clear SDS EU (THIS) Part B 942281 Revision date: - Issue date: 22-January-2018

Switzerland. SUVA Grenzwerte a Additional components	m Arbeitsplatz Type	Value	
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3	
` ,		1000 ppm	
	TWA	960 mg/m3	
		500 ppm	
UK. EH40 Workplace Exposure L	imits (WELs)		
Additional components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1920 mg/m3	
		1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Wear a face shield if there is a risk of

splashing.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

- Other Wear appropriate chemical resistant clothing, including apron and sleeves. Full body suit and

boots are recommended when handling large volumes or in emergency situations.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Observe any medical surveillance requirements. Always observe good personal hygiene

measures, such as washing after handling the material and before eating, drinking, and/or smoking. Remove contaminated clothing. Contaminated work clothing should not be allowed out of

the workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.

Colorless to yellowish.

Odour Amine-like.

Odour threshold Not available.

pH 11,3 at 20 °C

Melting point/freezing point <-70 °C (<-94 °F)

Initial boiling point and boiling 220 °C (428 °F)

range

Flash point 92,8 °C (199,0 °F)
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

CREATE FREE Clear SDS EU

(THIS) Part B 942281 Revision date: - Issue date: 22-January-2018

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 0.7 % Explosive limit - upper 17,5 %

(%)

0.02 hPa at 20 °C Vapour pressure Vapour density Not available. 0,95 g/cm3 Relative density 5,4 g/l at 20°C Solubility(ies)

Partition coefficient (n-octanol/water)

1,7 QSAR-method (20 °C)

300 °C (572 °F) **Auto-ignition temperature Decomposition temperature** Not available.

Viscosity 2 mPa·s DIN 53015 at 20 °C

Not explosive. **Explosive properties Oxidising properties** Not oxidising.

9.2. Other information

VOC < 100 g/I

SECTION 10: Stability and reactivity

10.1. Reactivity The product reacts with: Epoxy resins. 10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

Contact with water liberates ethanol. Polymerization will not occur unless product is mixed with

epoxy resins, isocyanates or urethane prepolymers. Exothermic reaction with acids. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents. Strong acids.

10.6. Hazardous

decomposition products

10.4. Conditions to avoid

Ethanol in case of hydrolysis. Thermal decomposition of this product can generate carbon

monoxide, carbon dioxide and nitrogen oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Causes digestive tract burns. Harmful if swallowed. Ingestion

Symptoms Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

Harmful if swallowed.

11.1. Information on toxicological effects

Acute toxicity Harmful if swallowed. Skin corrosion/irritation Causes severe skin burns. Causes serious eye damage. Serious eve damage/eve

irritation

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation May cause an allergic skin reaction.

Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Mixture versus substance No information available.

information

CREATE FREE Clear SDS EU (THIS) Part B 942281 Revision date: -Issue date: 22-January-2018 7 / 10

SECTION 12: Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the 12.1. Toxicity

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.2. Persistence and degradability

Biodegradability

Percent Degradation (Aerobic Biodegradation-Ready)

CREATE FREE Clear (THIS) Part B 67 % DOC; Die Away Test

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

CREATE FREE Clear (THIS) 1,7 QSAR-method, (20 °C)

> Part B The product is slightly soluble in water.

12.4. Mobility in soil Not a PBT or vPvB substance or mixture.

12.5. Results of PBT

and vPvB assessment

It will react with water and release ethanol.

12.6. Other adverse effects SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of Disposal methods/information

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Special precautions

SECTION 14: Transport information

ADR

UN3267 14.1. UN number

14.2. UN proper shipping

Corrosive liquid, basic, organic, n.o.s. (3-AMINOPROPYLTRIETHOXYSILANE)

14.3. Transport hazard class(es)

Class 8 Subsidiary risk 8 Label(s) 80 Hazard No. (ADR) **Tunnel restriction code** F 14.4. Packing group Ш 14.5. Environmental hazards No

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

RID

14.1. UN number

14.2. UN proper shipping Corrosive liquid, basic, organic, n.o.s. (3-AMINOPROPYLTRIETHOXYSILANE)

name

14.3. Transport hazard class(es)

8 Class Subsidiary risk 8 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN3267

CREATE FREE Clear SDS EU (THIS) Part B 942281 Revision date: -Issue date: 22-January-2018 8 / 10

14.2. UN proper shipping Corrosive liquid, basic, organic, n.o.s. (3-AMINOPROPYLTRIETHOXYSILANE)

name

14.3. Transport hazard class(es)

8 Class Subsidiary risk _ 8 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

IATA

14.1. UN number UN3267

Corrosive liquid, basic, organic, n.o.s. (3-AMINOPROPYLTRIETHOXYSILANE) 14.2. UN proper shipping

14.3. Transport hazard class(es)

8 Class Subsidiary risk 8 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards No **ERG Code**

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IMDG

UN3267 14.1. UN number

Corrosive liquid, basic, organic, n.o.s. (3-AMINOPROPYLTRIETHOXYSILANE) 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

8 Class Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards Marine pollutant Nο

F-A. S-B **EmS**

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

14.7. Transport in bulk Not applicable.

according to Annex II of MARPOL 73/78 and the IBC

Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed. Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed. Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

CREATE FREE Clear SDS EU (THIS) Part B 942281 Revision date: -Issue date: 22-January-2018

9 / 10

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Ethanol (CAS 64-17-5)

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Follow national regulation for work with chemical agents. Young people under 18 years old are not

allowed to work with this product according to EU Directive 94/33/EC on the protection of young

people at work, as amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

PBT: Persistent, bioaccumulative and toxic.

vPvB: Very Persistent and very Bioaccumulative.

TWA: Time weighted average. STEL: Short term exposure limit.

CEN: European Committee for Standardisation.

BCF: Bio Concentration Factor. VOC: Volatile organic compounds.

QSAR: Quantitative Structure Activity Relation.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

TLV: Threshold Limit Value. VLE: Exposure Limit Value VME: Exposure Average Value

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

References HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any H-statements not written out in full under

Sections 2 to 15

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

Training information

Follow training instructions when handling this material.

Disclaimer

IdeaPaint cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

CREATE FREE Clear SDS EU

(THIS) Part B 942281 Version #: 01