



Available only from the technology experts at SMART PARK

- 100% Waterproof (IP68 Tested)
- Camera with inbuilt Microphone
- Sony SuperHAD CCD image sensor.
- IR Night Illumination
- All Metal Heavy Duty Housing
- Stainless Steel Mounting Hardware
- Adjustable Sunshield Included
- Screwlock waterproof connectors
- Plug'n'Play with Zorg Monitors
- Three Year Warranty

| Item | CAM150 |
|-----------------------------|--|
| Image Type | Color CCD |
| Number of effective pixels | 500 (H) × 582 (V) approx. 0.29M pixels |
| Total number of pixels | 537 (H) × 597 (V) approx. 0.32M pixels |
| Image Size | Diagonal 4.5mm (Type 1/4") |
| Lens | Focal Length 3.6mm Maximum Aperture F2.0 |
| Angle of view | 110° diagonal |
| View angle (Horizontal) | 82° |
| View angle (Vertical) | 60° |
| Synchronization | Internal |
| Horizontal Resolution | 420 TV Line |
| Signal to Noise Ratio | 48dbm |
| Video signal (75ohm) | 1.0Vр-р |
| LUX | 0 LUX With IR LED (ON/OFF) |
| IR switch control | Photosensing automatic control |
| Audio input | Condenser Microphone |
| Power Requirements | DC 12V/24V |
| Power Consumption (Max) | 1.2W |
| Operating Temperature Range | -30° ~ +85° °C RH95% Max |
| Storage Temperature Range | -40° ~ +105° °C RH95% Max |
| Dimension | 82 (L) x 73 (W) x 58 (D) mm |
| Weight Approx | (Including Mounting Bracket) 380g |
| Vibration | 5.0G |
| Waterproof Grade | IP69K |



Point to Point Distributions 9/7-8 Len Thomas Place, Narren Warren VIC 3805

eMail: sales@ptpdist.com.au