



Adjustable Speaker w/ Tri-color LED



Learning Capability



16 Program Options  
incl. Front Active Learning Technology



Auto-Mute Function



Low Profile Paintable  
Push In (PI) Sensors



Front or Rear Install  
Adjustable Range 3ft-7ft

- The most advanced sensor system available.
- 2 or 4 Sensor / Front or Rear - one kit for all
- Automatic active learning front system - Active when you need it & silent when you don't.
- Adjustable range and sensitivity
- Installs into plastic or metal bumpers.
- Learning capability to ignore vehicle mounted objects
- Auto-mute function for use when towing
- Adjustable Audio/Visual display unit included with high quality speaker.
- Advanced Visual Display Available
- Low profile, small diameter sensors
- Self-diagnostic check on startup



OE Style Recessed Sensor Option

Item	PDC125PI	
Power Requirements	DC 12V	
Current Draw	<120mA	
The Number of Sensors	4 pcs	
Detecting Distance	0~200 cm	
Sensor Cable Length	6 m	
Operating Temperature Range	-30°C ~ +80°C	
Storage Temperature	-40°C ~ +100°C	
Ultrasonic Frequency	58 KHz	
Alarm Type	Speaker	
Supporter	Yes	
Mode	Rear/Front	
Setting Function	Rear/Front, 2/4 Sensor, Far/Near Range, High/Low Sensitivity	
Zone Range	Center	0~40~100~200 cm
	Side Sensor	0~40~80 cm
Response time	0.2S	