









A B C D 1512 1500 57 76 A 6mm - 6mm

Features

- High Efficiency SMD LEDs
- Tri-colour Selectable
- Flicker Free Driver
- 1-10V Dimming Control
- Upward and Downward light capable
- Linking kit included
- Seamless diffuser (optional)
- IPX output control compatible





Scan for app



1300 551 942

sales@integratedpower.net.au
*For full warranty terms and conditions visit www.integratedpower.net.au

The new LB Series Linear Batten offers a modern, clean design with a range of features and mounting options. They are a perfect archtectual fitting for reception areas, offices, lobbies and classrooms. Ideal for both retrofits and new installations.



Applications

- Receptions
- Offices
- Classrooms
- Feature Lighting
- Lobbies

Standard Specifications

- Rated Input Power: 45W
- Lumen Output: 4000lm 4700lm
- Colour Temperature: 3000K /4000K /5700K
- CRI Rating: CRI>80
- SDCM Rating: <6
- IP Rating: IP20
- Beam Angle: 110°
- Fitting Weight: 3.5kg
- Service Life: L70>50,000hrs

Option List

- DALI Dimming /DALI
- IPX Output Control (additional hardware required)

Models List

White / Tri-colour Selectable Black / Tri-colour Selectable LB45WHXKD01 LB45BKXKD01

Accessories

Uplighting Module Wire	L
Suspension Kit - White Wire	L
Suspension Kit - Black	L
Seamless Diffuser - 10m Roll	L
Seamless Diffuser - 30m Roll	L

B11UPXKN01 B45WSK02WH B45WSK02BK B1SD10M B1SD30M

IES Files

LB45WHXKD01 1500mm 4000K 45W









sales@integratedpower.net.au
*For full warranty terms and conditions visit www.integratedpower.net.au