

CASAMBI




Premiere Series


CASAMBI RGBW LED FLOODLIGHT 35W - SILVER



The Premiere Series of LED floodlights by Integrated Power brings you into the world of colour controlled smart lighting. Compatible with multiple smart control systems such as Casambi, DMX and more. The wide range of optics make even the most challenging projects possible. Available in RGBW, RGB and Tuneable White.

219.5(8.64")





Features

- · Heavy duty construction
- · High quality LED chips
- · Wide range of optics
- · Casambi enabled
- · Clear lens standard
- Honeycomb lens option ** (excludes 3.8° and 8° narrow optics)
- · Adjustable bracket included
- RGB & Tuneable white models available

Applications

- Facades
- Bridges
- Sports Arenas
- Special Events
- Advertising
- Signage
- · Commercial Buildings
- Landscapes











1300 551 942

sales@integratedpower.net.au

Standard Specifications

Rated Input Power: 30W / 240 Vac

• Lumen Output: 3,500lm (clear lens)

• Lumen Output: 2,450lm (honeycomb lens)

Colour Temp: RGBW (2200K)

• CRI Rating: CRI>80

• Operating Temperature: -30/+50°C

• EPA (Sail Area): 0.04m²

• Service Life: L70 / 77,000hrs

IP Rating: IP66IK Rating: IK08

Fitting weight: 3.7kg ± 0.3kg

Casambi Control

Option List

- DC Input Power/ DCV
- White CCT options * /3000K/ 4000K/ 5000K
- Honeycomb Lens /HCL

Models List

Silver / RGBW / 3.8 Degree Optic PSC30SIRGBW03 Silver / RGBW / 8 Degree Optic PSC30SIRGBW08 Silver / RGBW / 12 Degree Optic PSC30SIRGBW12 Silver / RGBW / 30 Degree Optic PSC30SIRGBW30 Silver / RGBW / 60 Degree Optic PSC30SIRGBW60 Silver / RGBW / 75 Degree Optic PSC30SIRGBW75 Silver / RGBW / 15x30 Degree Optic PSC30SIRGBW1530 Silver / RGBW / 20x60 Degree Optic PSC30SIRGBW2060

Accessories

Visor / Glare Shield PS35VISOR

*Casambi Installation

Casambi control is achieved through an external Casambi device connecting to the DMX control cable which will require a separate housing (not supplied).

IES Files

IES PS35SIRGBW03 35W 3.8deg

IES PS35SIRGBW08 35W 8deg

IES PS35SIRGBW12 35W 12deg

IES PS35SIRGBW30 35W 30deg

IES PS35SIRGBW60 35W 60deg

IES PS35SIRGBW75 35W 75deg

IES PS35SIRGBW1530 35W 15x30deg

IES PS35SIRGBW2060 35W 20x60deg











1300 551 942