

CASAMBI





Premiere Series


CASAMBI TUNEABLE WHITE LED FLOODLIGHT SILVER - 150W



The Premiere Series of LED floodlights by Integrated Power brings you into the world of colour controlled smart lighting. Compatible with multiple smart control systems such as Casambi, DMX and more. The wide range of optics make even the most challenging projects possible. Available in RGBW, RGB and Tuneable White.







Features

- · Heavy duty construction
- · High quality LED chips
- · Wide range of optics
- Casambi enabled
- · Clear lens standard
- Honeycomb lens(excludes 3.8° and 8° narrow optics)
- · Adjustable bracket included
- · RGB & RGBW models available

Applications

- Facades
- Bridges
- Sports Arenas
- Special Events
- Advertising
- Signage
- Commercial Buildings
- Landscapes











1300 551 942

Standard Specifications

Rated Input Power: 150W

• Lumen Output: 15,000lm (clear lens)

• Lumen Output: 10,500lm (honeycomb lens)

• Colour Temp: 2200K - 4000K

• CRI Rating: CRI>80

Operating Temperature: -30/+50°C

• EPA (Sail Area): 0.12m²

• Service Life: L70 / 77,000hrs

IP Rating: IP66IK Rating: IK08

Fitting weight: 10.0kg ± 0.3kg

Casambi Control

Option List

- DC Input Power/DCV
- Honeycomb Lens/HCL

Models List

Silver / TW / 3.8 Degree Optic PSC150SITW03 Silver / TW / 8 Degree Optic PSC150SITW08 Silver / TW / 12 Degree Optic PSC150SITW12 Silver / TW / 30 Degree Optic PSC150SITW30 Silver TW / 60 Degree Optic PSC150SITW60 Silver / TW / 75 Degree Optic PSC150SITW75 Silver / TW /15x30 Degree Optic PSC150SITW1530 Silver / TW / 20x60 Degree Optic PSC150SITW2060

Accessories

Visor / Glare Shield PS35VISOR

*Casambi Installation

Casambi control is achieved through an external Casambi device connecting to the DMX control cable which will require a separate housing (not supplied).

IES Files

IES PS150SITW03 4K 150W 3.8deg
IES PS150SITW08 4K 150W 8deg
IES PS150SITW12 4K 150W 12deg
IES PS150SITW30 4K 150W 30deg
IES PS150SITW60 4K 150W 60deg
IES PS150SITW75 4K 150W 75deg
IES PS150SITW1530 4K 150W 15x30deg
IES PS150SITW2060 4K 150W 20x60deg











1300 551 942