



Premiere Series


DMX CONTROLLED RGBW LED FLOODLIGHT - 150W SILVER



Features

- Heavy duty construction
- High quality LED chips
- Wide range of optics
- 3-pin DMX in & out control cables
- Clear lens standard
- Honeycomb lens option** (excludes 3.8° and
- 8° narrow optics)
- U Bracket included
- RGB & Tuneable white models available

The Premiere Series of LED floodlights by Integrated Power brings you into the world of colour controlled smart lighting. Compatible with multiple smart control systems such as Casambi, DMX and more. The wide range of optics make even the most challenging projects possible. Available in RGBW, RGB and Tuneable White.



Applications

- Facades
- Bridges
- Sports Arenas
- Special Events
- Advertising
- Signage
- Commercial Buildings
- Landscapes









* For full warranty terms and conditions visit www.integratedpower.net.au

Date : 05-01-2023

Standard Specifications

- Rated Input Power: 150W / 240Vac
- Lumen Output: 15,000lm (clear leans)
- Lumen Output: 10,500lm (honeycomb lens**)
- Colour Temp: RGBW (2200K*)
- CRI Rating: CRI>80
- Operating Temperature: -30/+50 deg C
- EPA (Sail Area): 0.12m2
- Service Life: L70 / 77,000hrs
- Ingress Protection: IP66
- IK Rating: IK08
- Fitting weight: $10.0 \text{kg} \pm 0.3 \text{kg}$

Models List

Silver / RGBW / 3.8 Degree Optic Silver / RGBW / 8 Degree Optic Silver / RGBW / 12 Degree Optic Silver / RGBW / 30 Degree Optic Silver / RGBW / 60 Degree Optic Silver / RGBW / 75 Degree Optic Silver / RGBW / 15x30 Degree Optic Silver / RGBW / 20x60 Degree Optic PS150SIRGBW03 PS150SIRGBW08 PS150SIRGBW12 PS150SIRGBW30 PS150SIRGBW60 PS150SIRGBW75 PS150SIRGBW1530 PS150SIRGBW2060

Options List

- DC Input Power /DCV
- White CCT options*/3000K / 4000K /5000K
- Honeycomb Lens** /HCL

Special Order Special Order

Accessories

Visor / Glare Shield

PS150VISOR

IES Files

IES PS150SIRGBW03 150W 3.8deg IES PS150SIRGBW08 150W 8deg IES PS150SIRGBW12 150W 12deg IES PS150SIRGBW30 150W 30deg IES PS150SIRGBW60 150W 60deg IES PS150SIRGBW75 150W 75deg IES PS150SIRGBW1530 150W 15x30deg IES PS150SIRGBW2060 150W 20x60deg







