


WP Series

EMERGENCY WEATHERPROOF LED BATTEN - 40W/3W 1200MM



The WP Series emergency LED battens are a reliable, high quality weatherproof luminaire. This IK65 & IK08 rated luminaire is extremely robust and built for outdoor commercial applications. The wide light distribution and colour temperature switch allows you to easily match existing lights. The ideal replacement for surface mounted fluorescent fittings and new fitouts.



SPACING TABLE & MOUNTING HEIGHTS - AS / NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX)

Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m	6.0m	7.0m	8.0m
D25	11.5	13.2	14.8	15.7	16.1	16.4	16.8	17.3	17.6	18.1	18.3	18.2
D50	11.5	13.2	14.8	16.5	18.1	19.8	21.8	22.5	23.1	24.1	24.9	25.4

Features

- Robust Construction
- Stainless Steel Mounting Clips
- Locking screws
- Ceiling or wall mountable
- Frosted Diffuser
- Colour temperature selectable
- AS/NZS 2293.3 compliant
- Replaces 2x 36W Fluoro

Applications

- Council Facilities
- Car Parks
- Stairwells
- Parks
- Schools
- Exterior Walls/Ceilings
- Commercial Buildings



Standard Specifications

- Input Voltage: 200-240Vac
- Rated Input Power: 40W (Mains)
- Emergency Power: 3.5W ± 0.5W (Emerg)
- Battery Type: LiFePO4 6.4V 1500mAh
- Duration: 3hrs @ 3.5W
- Lumen Output: 3400lm - 4200lm
- CRI Rating: CRI>80
- Beam Angle: 120°
- C0 Classification: D50
- C90 Classification: D25
- IP Rating: IP65
- IK Rating: IK08
- Fitting Weight: 1.95kg

Option List

- DALI Driver / DALI

Models List

Grey / 3CCT / 1200MM

WPE40GRXKN01

Accessories

IES Files

IES WP40GR4KN01 40W

