SAFETY DATA SHEET

1. Identification

Product identifier IdeaPaint CREATE CLEAR THIS (Part B)

Other means of identification None.

Recommended use Dry erase coating.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier IdeaPaint

40 Broad Street, 1st Floor

Boston, MA 02109

Telephone number 617.714.1050

e-mail marty@ideapaint.com

Emergency +1.866.519.4752 (US, Canada, Mexico)

+1-760-476-3962 (US, Canada, Mexico)

Access Code: 333641

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 1BSerious eye damage/eye irritationCategory 1Sensitization, skinCategory 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Harmful if swallowed. Causes severe skin burns and eye damage. May cause

an allergic skin reaction.

Precautionary statement

Prevention Keep away from flames and hot surfaces-No smoking. Do not breathe mist or vapor. Wash

thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse. In case of fire: Use water fog, foam, dry chemical powder, carbon dioxide (CO2) to

extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

IdeaPaint CREATE CLEAR THIS (Part B)
909941 Version #: 01 Revision date: - Issue date: 19-October-2017

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
3-Aminopropyltriethoxysilane	919-30-2	99

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Provide eyewash station. Eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison

control center immediately.

Harmful if swallowed.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction, Dermatitis, Rash, Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Combustible liquid. Will burn if involved in a fire.

Issue date: 19-October-2017

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

IdeaPaint CREATE CLEAR THIS (Part B) 909941 Version #: 01 Revision date: -

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

_

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Persons susceptible to allergic reactions should not handle this product. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Additional components	Туре	Value	
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3	
,		1000 ppm	
US. ACGIH Threshold Limit Value	es		
Additional components	Type	Value	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Additional components	Type	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	

Biological limit values Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

UC COLLA Table 7.4 Limits for Air Contenting outs (00 OFD 4040 4000)

Eye/face protection	Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes.
---------------------	--

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Skin protection

Other Wear appropriate chemical resistant clothing, including apron and sleeves. Full body suit and

boots are recommended when handling large volumes or in emergency situations.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Remove contaminated clothing. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.

Color Colorless to yellowish.

Odor Amine-like.
Odor threshold Not available.
pH 11.3 at 20 °C

Melting point/freezing point $< -94 \,^{\circ}\text{F} \,(< -70 \,^{\circ}\text{C})$ Initial boiling point and boiling $428 \,^{\circ}\text{F} \,(220 \,^{\circ}\text{C})$

range

Flash point 199.0 °F (92.8 °C)
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Explosive limit - lower (%) 0.8 % Explosive limit - upper (%) 4.5 %

Vapor pressure0.02 hPa at 20 °CVapor densityNot available.Relative density0.94 g/cm³

Solubility(ies)

Solubility (water) 5.4 g/l at 20°C

Partition coefficient 1.7 QSAR-method (20 °C)

(n-octanol/water)

Auto-ignition temperature 572 °F (300 °C) **Decomposition temperature** Not available.

Viscosity 2 mPa·s DIN 53015 at 20 °C

Other information

Explosive properties

Molecular formula

C9-H23-N-O3-Si

Molecular weight

Cxidizing properties

Pounds per gallon

VOC

Not explosive.

C9-H23-N-O3-Si

And in the properties

Not oxidizing.

7.88 lbs/gal

< 100 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

Contact with water liberates ethanol. Polymerization will not occur unless product is mixed with

epoxy resins, isocyanates or urethane prepolymers.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition

products

Ethanol in case of hydrolysis. Thermal decomposition of this product can generate carbon

monoxide, carbon dioxide and nitrogen oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Causes severe skin burns. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

SDS US

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract. Harmful if swallowed.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Toxicological data

Additional components Species Test Results

Ethanol (CAS 64-17-5)

Acute Inhalation Vapor

LC50 Mouse 39 g/m3, 4 Hours

Oral

LD50 Rat 7000 - 11000 mg/kg

Skin corrosion/irritation Serious eye damage/eye irritation Causes severe skin burns.
Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Further information Symptoms may be delayed. Ethanol may be released.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Additional components

Species

Test Results

Ethanol (CAS 64-17-5) Aquatic Acute Crustacea LC50 Ceriodaphnia dubia 5012 mg/l, 48 hours Daphnia magna 454 mg/l, 11 days Fish LC50 Pimephales promelas 13480 mg/l, 96 hours Chronic Crustacea NOEC Ceriodaphnia dubia 9.6 mg/l, 10 days

Persistence and degradability

IdeaPaint CREATE CLEAR THIS (Part B)
909941 Version #: 01 Revision date: - Issue date: 19-October-2017

Biodegradability

Percent degradation (Aerobic biodegradation-ready)

IdeaPaint CREATE CLEAR THIS (Part B) 67 % DOC; Die Away Test

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

IdeaPaint CREATE CLEAR THIS (Part B) 1.7 QSAR-method, (20 °C)

The product is slightly soluble in water. Mobility in soil It will react with water and release ethanol. Other adverse effects

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN3267 **UN number**

UN proper shipping name Corrosive liquid, basic, organic, n.o.s.

Transport hazard class(es)

Class 8 Subsidiary risk 8 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B2. IB2. T11. TP2. TP27

Packaging exceptions 154 202 Packaging non bulk Packaging bulk 242

IATA

UN number UN3267

UN proper shipping name

Transport hazard class(es)

Corrosive liquid, basic, organic, n.o.s. (3-AMINOPROPYLTRIETHOXYSILANE)

Class 8 Subsidiary risk 8 Label(s) П Packing group Nο **Environmental hazards ERG Code** 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3267

UN proper shipping name Corrosive liquid, basic, organic, n.o.s. (3-AMINOPROPYLTRIETHOXYSILANE)

Transport hazard class(es)

8 Class Subsidiary risk Packing group Ш **Environmental hazards**

Marine pollutant No F-A, S-B **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IdeaPaint CREATE CLEAR THIS (Part B) 909941 Version #: 01 Revision date: -Issue date: 19-October-2017 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS 64-17-5) Low priority

US state regulationsCalifornia Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. Massachusetts RTK - Substance List

Ethanol (CAS 64-17-5)

US. New Jersey Worker and Community Right-to-Know Act

Ethanol (CAS 64-17-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethanol (CAS 64-17-5)

US. Rhode Island RTK

Ethanol (CAS 64-17-5)

California Proposition 65

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethanol (CAS 64-17-5) Listed: October 1, 1987

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region Inventory name On inventory (yes/no)*

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

Yes

New Zealand New Zealand Inventory Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 19-October-2017

Revision date - 01

NFPA ratings



List of abbreviations TWA: Time weighted average.

STEL: Short term exposure limit.

CEN: European Committee for Standardisation.

BCF: Bio Concentration Factor. VOC: Volatile organic compounds.

QSAR: Quantitative Structure Activity Relation.

Disclaimer IdeaPaint cannot anticipate all conditions under which this information and its product, or the

products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

IdeaPaint CREATE CLEAR THIS (Part B)