

Submittal Sheet

Model 100SS-R Horizontal Recessed Full-Body Stainless Steel Diaper Changing Station

- Full body 16 gauge, 304 brushed stainless steel.
- ABS replaceable tray liner / changing surface.
- Smooth nylon belt with Thermoplastic Polyurethane coating. Easy to sanitize and adjustable with one hand.
- Full stainless steel frame and hinges provide maximum durability.
- Easy to read ANSI compliant labels (ANSI Z535.3 and ANSI Z535.4), utilizing universal safety symbols.
- Includes universal changing station door sign.
- Pneumatic gas shock mechanism to ensure smooth, safe open and close motions.
- Recess-mounted installation. Hardware included.
- Limited Warranty: This product is warranted against manufacturing defects for a period of 5 years.

Short Specifications

Full 304 brushed stainless steel exterior with replaceable, vacuum-formed ABS changing surface. Recess-mounted.

- 1. A.D.A Compliant attached safety strap with cam-buckle.
- 2. Acceptable product: Foundations Worldwide, Inc.; Model 100SS-R (Full SS Horizontal Recessed Mount).

3. Characteristics:

- a. Entire body 16 gauge, 304 brushed stainless steel, seamless welds.
- 4. Equipped with a pneumatic cylinder.
- 5. Smooth nylon belt with Thermoplastic Polyurethane coating. Easy to sanitize and adjustable with one hand.
- 6. Meets ASTM F2285 requirements for weight bearing Commercial Changing Stations.
- 7. A.D.A. Compliance:
- E
- 306.3 Knee Clearance 307.2 Maximum Protruding Objects 308.2 Forward Reach 308.3 Side Reach 309.4 Operation 902.3 Work Surface Compliant when properly installed.
- 8. ANSI compliant safety labels.
- CPSIA compliant to applicable sections.

Installation Information

- Unit recesses into wall 3-7/8" (98 mm); closed unit projects from wall 1" (25 mm).
- Rough-in opening to be 34-1/2" (876 mm) wide x 21-3/4" (552 mm) high. Shim as required for tight fit on all four sides. Use side mounting holes.
- Open unit projects from wall 18" (457 mm) when in use.

SI268D