

## Hand Dryer Series

## **Description: HK-1800PS**

Push-button operation hand dryer.
Casing:made of high grade fire retardant
ABS, 3.0 mm thick
Brush motor:80W,2850 R.P.M.(50Hz)

3400 R.P.M.(60Hz) Heater assembly:

Designed with 105°C(221°F)thermostat.

Designed with 87°C(200°F)thermostat.

Designed with 141°C(323°F)thermal cut-off.

Sound level:55 ± 3db

Approximately 20 25 accords drying time

Approximately 30-35 seconds drying time.



Dryer shall deliver 291 m<sup>3</sup>/h(171CFM)–60Hz. 255 m<sup>3</sup>/h(150CFM)–50Hz.

Adjustable timer control range from 20 to 55 seconds.

Power cut off automatically in case of irregular use over 120 seconds.

Drip proof:IPX1

WEIGHT: 3.8 kgs (8.4lbs) unpacked: 4.5 kgs (9.9lbs) packed.

## **Specifications and Dimensions**

				Housing Dimension: mm (in)		
Model	Volts	Watts	Amps	VV	Н	D
	120Vac	1800W	15A	268(10 1/2)	220(8 3/4	170(6 3/4)
HK-1800PS	220Vac	1800W	8.2A	268(10 1/2)	220(8 3/4	170(6 3/4)
	230/240Vac	1653-1800W	7.2-7.5A	268(10 1/2)	220(8 3/4	170(6 3/4)





