

Hand Dryer Series >> Surface Mounting >> TOUCH FREE

Item No. HK-1800SA

Casing : Stainless SteelMaterial : Stainless Steel

Operation Power: 1800 W

· Automatic operation hand dryer

- Casing: Stainless steel satin finished. (#304 1.2 mm thick)
- Brushless motor: 100W, 2850 R.P.M.(50Hz), 3250 R.P.M.(60Hz)
- Motor: Designed with 105 degree C (221 degree F) thermostat
- Heater assembly: Designed with 70 degree C (158 degree F) thermostat and Designed with 139 degree C (282 degree F) thermal cut-off
- Dryer shall deliver 291 m3/h (171CFM)--60Hz, 255 m3/h (150CFM)-50Hz
- Air speed: 16.5m/s--60Hz, 14.5m/s--50Hz; Sound level: 63 +/- 3 db (for brushless motor)
- Approximately 30-35 second drying time (For brushless motor)
- Adjustable sensitive distance of sensor from 10 to 30 CM
- Power cut off automatically in case of irregular use over 60 seconds
- 2 vandal-proof lock screws and key wrench
- Drip proof: IPX1



Specifications and Dimensions

- Volts: 110-120 Vac, Watts: 1512-1800W, Amps: 13.8-15A
- Volts: 220-240 Vac, Watts: 1512-1800W, Amps: 6.9-7.5A
- Housing Dimensions:
- 240 mm (W) x 216 mm (H) x 1650 mm (D)
- 9-3/8" (W) x 8-1/2" (H) x 6-1/2" (D)
- Weight: 5.4 kg (11.9 lbs) unpacked, 6.4 kg (14.1 lbs) packed

HOKWANG INDUSTRIES CO., LTD.

NO. 131, TING PING ROAD, JUEI-FANG INDUSTRIAL AREA, JUEI-FANG TOWN, TAIPEI COUNTY 224, TAIWAN. R.O.C.
Tel: 886-2-2496 6425 Fax: 886-2-2496 6538
E-mail:hokwang@hokwang.com
Person to contact: James Hsu