

CODE NUMBER

3366131

DESCRIPTION

Sloan Optima® Air Sensor-Operated Wall - Surface - ADA Hand Dryer EHD-702 208/277V, Sloan Optima® Air Sensor-Operated Wall - Surface - ADA Hand Dryer.

DETAILS

• Finish: Brushed Nickel (BN)

Voltage: 208/277VWattage: 50/60HzAmperage: 3.6-4.0

• Mounting: Wall - Surface - ADA

Power Type: HardwiredDepth: 4" (102mm)

Height: 13 93/100" (354mm)Width: 9 39/250" (233mm)

FEATURES

• Hygienic hand drying solution

• 14 second dry time

• Electric Specifications: 208-277V 5.6 - 6.2A

• Meets ADA requirements without the need of a recess kit

• Adjustable speed and sound (High-Low)

Adjustable Heat (High-Low-Off)

• 95% cost savings vs. paper towels

• Weight: 8-10 lbs.

• Vandal resistant cover design

 Suggested Mounting Heights for Ideal Performance (from floor to bottom of dryer): Men: 45" (114 cm), Women: 43" (109 cm), Teenagers: 41" (104 cm), Children: 35" (89 cm), ADA: 37" (94 cm). Note: When mounting for any user ensure that it is mounted below the 48" ADA Maximum

Available in Polished White and Brushed Nickel

• 35-second lockout feature if hands are not removed

• Externally visible Red LED light that flashes error codes to assist in troubleshooting and identify if filter has been clogged

• Virtually maintenance free


 Air temperature of up to 141°F (61°C) at a 72°F (22°C) ambient room temperature at the hands (4 inches [102 mm] below air outlet).

 Quantity Recommendations: 1 dryer for every 2 sink stations is sufficient for most applications. For high traffic applications we suggest 1 dryer per sink station.

• Variations: Available in 2 finishes/colors

• Optional Add Ons: Wall Guards (White, Black, Stainless)





COMPLIANCES & CERTIFICATIONS









(BAA Compliant, Proposition 65, cUL Certified, UL Certified)

RECOMMENDED SPECIFICATION

EHD-702 Brushed Nickel Finish, 208V

NOTES

All information contained within this document subject to change without notice.