DATA SHEET Kit for recessed Machflous



KT009CS

General Description

- Kit for recessing the machflow® (M03) series hand dryer (hand dryer not included).
- The recess kit for the machflow® series hand dryer makes the machflow® compliant with the ADAAG norm (US) which limits to 4" the horizontal projection of devices installed anywhere between 27" and 80" above the floor within main traffic cooridor of a public restroom. By recessing the hand dryer, it can be said of the hand dryer that it is "specific for the disabled".
- Built for maximum durablility and to be virtually vandal-proof.
- Seamlessly integrates into the aesthetics of any washroom environment.

Components & Materials

- KT009CS:stainless steel AISI 304 kit for recessed machflow® hand dryer (hand dryer not included), satin finish. Made of two main parts: cabinet and frame.
- **CABINET**: the cabinet consists of two welded pieces. The dryer mounting areas are fabricated of 18GA 18-8 type ASAI 304 stainless steel and include four (4) M5 bolts welded to and projecting from the base plate for attaching the machflow® hand dryer.
- FRAME: made from 22GA 18-8 type AISI 304 stainless steel with four (4) screw holes of Ø 1/4" (6.5 mm) for mounting on the wall.
- Nuts and bolts for attaching the hand dryer to the kit are included: four (4) nuts DIN 934 M5, four (4) washers DIN 9021 M5, and four (4) rubber silent blocks 8 x 18 mm.

NOTE 1: Machflow hand dryer not included.

NOTE 2: The screws and wall plugs for the mounting of the cabinet to the wall are not included. The use of stainless steel screws is recommended.

Technical Specifications

Cabinet dimensions - 23 3/8" H x 14 3/4" W x 3" D	Rough Wall Opening - 21 5/8" H x 13" W x 3 3/8" D
Outer projection from the wall - 3 55/64"	Wall accommodation - 3 3/8" depth

Operation

No specific instructions for its use required.

Please mark the selected item



code KT009CS

material stainless steel finish satin

Installation

Verify all rough-in dimensions prior to installation and proceed to install according to the dimensions recommended in the figures.

Guide specification

Kit for recessed machflow® hand dryer (hand dryer not included) consisted in two main parts: a cabinet and a frame. Cabinet should be made in two welded parts. The dryer mounting areas are fabricated of 18GA 18-8 type AISI304 stainless steel, it includes 4 M5 bolts welded on top of the base plate for fitting of the machflow® hand dryer. The frame is made in 22GA 18-8 type AISI304 stainless steel with 4 screw holes of \emptyset 1/4" (6,5mm) for mounting on the wall. Nuts and bolts for the fitting of the hand dryer to the kit included: 4 nuts DIN 934 M5, 4 washers DIN 9021 M5 and 4 rubber silent blocks 8 x 18mm.

Kit for recessing the machflow® hand dryer should be model KT009CS, frame in stainless steel AISI 304, satin finish, manufactured by Saniflow Corp., 3325 NW 70th Avenue, Miami, FL 3312, USA.


Overall dimensions:

KT009CS:

23 3/8" H x 14 3/4" W x 3" D.


Weight: 6.6 lbs (3 Kg) without Machflow hand dryer

MOUNTING




KT009CS


Serial mounting



Recommended heights from floor



	Male	Female	Child	Disabled
A To metal frame	38 7/8" (99cm)	36 7/8" (94cm)	29" (74cm)	31" (79cm)
B To wall opening	39 3/4" (101cm)	37 3/4" (96cm)	29 7/8" (76cm)	31 7/8" (81cm)
C To sensor top	47 5/8" (121cm)	45 5/8" (116cm)	37 3/4" (96cm)	39 3/4" (101cm)
D To electrical entry point	55 1/8" (140cm)	53 1/8" (135cm)	45 1/4" (115cm)	47 1/4" (120cm)
E To top of machine	60 1/4" (153cm)	58 1/4" (148cm)	50 3/8" (128cm)	52 3/8" (133cm)



Job:	Architect / Engineer:	City / State / Country:
Model number:	Contractor:	Date:
Variations:	Customer / Wholesaler:	Quantity:

Saniflow Corp reserves the right to make changes and/or modifications to the products and their specifications without warning or notice.